

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b>  G06F 17/60	<b>A1</b>	<b>(11) International Publication Number:</b> WO 99/60504  <b>(43) International Publication Date:</b> 25 November 1999 (25.11.99)
<b>(21) International Application Number:</b> PCT/US99/10707  <b>(22) International Filing Date:</b> 14 May 1999 (14.05.99)  <b>(30) Priority Data:</b> 09/080,165 15 May 1998 (15.05.98) US 09/237,718 26 January 1999 (26.01.99) US  <b>(71) Applicant:</b> UNICAST COMMUNICATIONS CORPORATION [US/US]; 9th floor, 650 Fifth Avenue, New York, NY 10019 (US).  <b>(72) Inventors:</b> LANDSMAN, Rick, W.; 8 Rampart Pass, Waccabuc, NY 10597 (US). LEE, Wei-Yeh; Apartment 9-C, 140 W. 58th Street, New York, NY 10019 (US).  <b>(74) Agent:</b> MICHAELSON, Peter, L.; Michaelson & Wallace, Parkway 109 Office Center, 328 Newman Springs Road, P.O. Box 8489, Red Bank, NJ 07701 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> A TECHNIQUE FOR IMPLEMENTING BROWSER-INITIATED NETWORK-DISTRIBUTED ADVERTISING AND FOR INTERSTITIALLY DISPLAYING AN ADVERTISEMENT  <b>(57) Abstract</b>  A technique for implementing in a networked client-server environment, network-distributed advertising in which advertisements are downloaded from an advertising server to a browser executing at a client computer and subsequently displayed by that browser on an interstitial basis, in response to a click-stream generated by the user. An HTML advertising tag is embedded into a referring web page. This tag contains two components. One component effectively downloads from a distribution web server and persistently instantiates an agent at the client browser which downloads advertising files originating from an AD management system residing on a third-party advertising web server, for a given advertisement into browser cache and subsequently plays those media files through the browser on an interstitial basis. The other component is a reference of the advertising management system. This latter reference totally "decouples" advertising content from a web page such that a web page, merely includes an advertising tag that refers, via a URL, to a specific AD management system. The AD management system selects the given advertisement that is to be downloaded.		

AD

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

-1-

A TECHNIQUE FOR IMPLEMENTING BROWSER-INITIATED NETWORK-DISTRIBUTED ADVERTISING AND FOR  
INTERSTITIALLY DISPLAYING AN ADVERTISEMENT

BACKGROUND OF THE DISCLOSURE

1. Field of the Invention

5           The invention relates to a technique,  
specifically apparatus and accompanying methods, for  
implementing in a networked client-server environment,  
such as the Internet, network-distributed advertising in  
which an advertisement is downloaded, from an advertising  
10   server to a web browser executing at a client computer,  
in a manner transparent to a user situated at the  
browser, and subsequently displayed, by that browser and  
on an interstitial basis, in response to a click-stream  
generated by the user to move from one web page to the  
15   next.

2. Description of the Prior Art

20           Currently, Internet usage, and particularly  
that of the World Wide Web (henceforth referred to as  
simply the "web"), is growing explosively, particularly  
as the number of web sites and users that have access to  
the Internet continue to rapidly and to a great extent,  
exponentially, expand.

-2-

In essence, after establishing a suitable network connection to the Internet, a user at a client computer can easily employ a graphical web browser, such as the Internet Explorer ("IE") browser presently  
5 available from Microsoft Corporation of Redmond, Washington, to connect to a web site and then download a desired web page by simply supplying a specific address (known as a URL or uniform resource locator) of that page to the browser. The URL identifies both an address of  
10 the site, in terms of its Internet domain name, and a page of information at that site, in terms of its corresponding file name. Each web site stores at least one, and often times substantially more pages all arranged in a pre-defined hierarchy, generally beginning,  
15 at its root, with a so-called "home page". Each such page is written in HTML (hypertext markup language) form. A page, in this context, refers to content accessed via a single URL, including, e.g., text, graphics and other information specified in HTML code for that particular  
20 page. Once a user supplies a URL of interest, the browser operated by that user sends an appropriate command, using a TCP/IP protocol (transmission control protocol/internet protocol), to a remote HTTP (hypertext transport protocol) server, located at the web site and  
25 which stores that page, to access and download a corresponding file for that page. In response, the server then sends, using the TCP/IP protocol, a stored file containing HTML code that constitutes that page back to the browser. As the file that constitutes the page  
30 itself is received by the browser, the browser interprets and executes the HTML code in that file to properly

-3-

assemble and render the page on, e.g., a monitor to a user situated at the client computer. Such a page may itself contain HTML commands that reference other files, residing on the same or different web sites, which, when these commands are appropriately interpreted and executed by the browser, result in those files being downloaded and their resulting content properly assembled by the browser into the rendered page. Once all the content associated with the page is rendered, the user can then position his(her) mouse cursor on a suitable hypertext link, button or other suitable user input field (whichever here implements a "hotlink") displayed on that page and then, through, e.g., a mouse "click", effectively download a file for and render another desired page in succession until the user has finished his(her) visit to that site, at which point, the user can transition through a hotlink to a page at another site, and so forth. A hotlink specifies a complete web address of an associated page, including a domain name of its hosting web site at which that page is situated. Consequently, by simply and successively positioning and "clicking" his(her) mouse at an appropriate hotlink for each one of a number of desired web pages, the user can readily retrieve an HTML file for each desired page in succession from its corresponding web site and render that page, and, by doing so, essentially effortlessly jump from site to site, regardless of where those sites are physically located.

Ever since their introduction several years ago, HTML and accompanying browser software, now

-4-

including, e.g., attendant programming languages such as Java and JavaScript languages ("Java" is a registered trademark of Sun Microsystems in Mountain View, California; "JavaScript" is a trademark of Netscape Communications in Mountain View, California), have undergone rather rapid and continual evolution. A major purpose of which has been and continues to be to provide web page authors with an ability to render increasingly rich content through their pages and, as a result, heighten a "user experience" for those users who visit these pages. Consequently, web pages are no longer limited to relatively simple textual displays -- as occurred with early versions of HTML and browser software, but can now encompass even full-motion multimedia presentations and interactive games that use rather sophisticated graphics.

The simplicity of browsing the web coupled with the relative low-cost of accessing the Internet, and the relative ease through which a web site can be established are collectively fueling unparalleled growth and diffusion of the Internet itself, web sites and the Internet user community throughout the world. In that regard, by establishing web sites, merchants, vendors and other information providers have an unparalleled opportunity, basically unheard of as little as 5-10 years ago, to reach enormous numbers of potential consumers -- regardless of where these consumers reside -- at costs far less than previously thought possible. Moreover, given the staggering amount and wide diversity of information currently available on the web, web browsing

-5-

is becoming so popular a past-time for sufficient numbers of individuals that browsing is beginning to divert significant viewership away from traditional forms of mass entertainment, such as television and cable. While  
5 such diversion is relatively small at present, it is likely to rapidly grow. Moreover, given the ease and convenience with which users, situated at their personal computers and with basically nothing more complicated than a few mouse clicks, can effectively interact with  
10 remote web sites, electronic commerce, through which goods and services are ordered through the Internet without ever visiting a physical store, is rapidly emerging as a significant sales medium. This medium is likely to significantly challenge and possibly, over a  
15 relatively short time, may even alter traditional forms of retailing.

Given the wide and ever-growing reach of the web as a source of consumer information and the  
20 increasing consumer acceptance of electronic commerce, advertisers have clearly recognized the immense potential of the web as an effective medium for disseminating advertisements to a consuming public.

25 Unfortunately, conventional web-based advertising, for various practical reasons -- some being technical in nature and others relating to a nature of traditional web advertisements themselves, has generally yielded unsatisfactory results and thus has usually been  
30 shunned by most large advertisers. In that regard, several approaches exist in the art for implementing web

-6-

based advertisements. However, all suffer serious limitations of one form or another that have sharply restricted their desirability and use.

5                   Currently, a predominant format, referred to as  
a "banner", for a web advertisement takes the form of a  
rectangular graphical display situated, typically at a  
fixed location, in a rendered web page. A banner, which  
can be static or animated, can be situated anywhere  
10                   within a rendered web page but most often is situated at  
a top or bottom, or along a vertical edge of that page.  
A banner, depending on its size, can extend across an  
entire page width or length, and usually contains, in a  
graphical eye-catching form, a name of a product or  
15                   service being advertised. Increasingly, a banner for a  
given product or service implements a hotlink to enable a  
consumer to "click-through" the banner (i.e., generate a  
mouse click on the banner) in order to transition, via  
his browser, to a web site maintained by a corresponding  
20                   advertiser and, from that site, fetch a web page to  
provide additional information regarding that product or  
service. Hence, the consumer could easily obtain more  
information by a click-through; while an advertiser,  
monitoring counts of such click-throughs that occur in a  
25                   given period of time, could gain feedback on the  
effectiveness of the corresponding banner.

                  A banner is generally produced by properly  
embedding specific HTML code for that banner within the  
30                   HTML coding for a given web page in which the banner is  
to appear. A client browser, as it interprets and

-7-

sequentially executes the HTML code for a fetched page, will, in turn, compile and execute the embedded code for the banner and hence display the banner, as part of a rendered page and at a specified location thereon.

5

In implementing a banner, whether static or even animated, its HTML coding generally involved downloading an appropriate file, for that banner, to a client browser. The file may be stored on the same server that stores the HTML file for the page, or  
10 accessed from a remote server. The file may contain a graphic itself, such as in a GIF (graphic interchange format) file, or a Java applet which, once interpreted and executed by the browser, generates and renders a  
15 desired animated graphic. This file, whether it be a graphic or applet, requires time to download and must be downloaded and assembled by the browser on the page prior to that page being fully rendered. The download time for that file, particularly as it increases in size, clearly,  
20 a priori, lengthens a time interval during which that page would completely download, thereby extending the time to fully render the page, including the banner, after a user transitioned to that page. Channel bandwidth to a client computer (e.g., personal computer  
25 -- PC), such as that provided through a modem connection, is often rather limited. Consequently, if the file size for the banner were relatively large -- as would certainly be the case for relatively "rich" content, e.g., audio or video content, the delay in downloading  
30 such a file over such a limited bandwidth connection could be excessive, and consequently highly frustrating

-8-

to the user. Hence, a user would likely wait a considerable amount of time before all the page components for multimedia content are fully downloaded to permit that page to be rendered. Such delay, if  
5 encountered during a page transition, can be rather frustrating to a user, even to the point at which the user, just to end his(her) waiting, will prematurely terminate the download and transition to another page. Therefore, in an effort to preserve an appropriate  
10 "editorial experience" for a user, content suppliers sharply limit the file size, of such banners to be rendered on their pages, in order to minimize page download and hence latency times.

15 Unfortunately, such restricted file sizes effectively limit the richness of the content of a banner to a rather simplistic advertisement -- even with animation. Thus, banners often failed, as advertisers soon recognized by relatively low click-through counts,  
20 to attract sufficient viewer attention to justify their use and expense.

In an effort to overcome the content limitation associated with banners, the art teaches the use of a  
25 different advertising modality: so-called "interstitial" advertisements. See, e.g., United States patent 5,305,195 (issued to A. J. Murphy on April 19, 1994 -- hereinafter the "Murphy" patent) which discloses the concept of using interstitial advertisements though not  
30 in the context of web advertising. As described in the Murphy patent, pre-stored advertisements are displayed at

-9-

specific intervals on each one of a group of networked ATM (automated transaction machines) terminals. In particular, the advertisements are downloaded, either directly or via a server, from a remote computer and locally stored on each such terminal and subsequently displayed on that terminal while it waits for a response, from a remote mainframe transaction server, to a transaction initiated at that terminal.

Generally speaking and with specific reference to web advertising, interstitial ads are displayed in an interval of time that occurs after a user has clicked on a hot-link displayed by a browser to retrieve a desired web page but before that browser has started rendering that page. Such an interval, commonly referred to as an "interstitial", arises for the simple reason that a browser requires time, once a user clicks on a hotlink for a new page, to fetch a file(s) from a remote web server(s) for that particular page and then fully assemble and render that page. The length of an interstitial interval, which is quite variable, is governed by a variety of factors, including, e.g., a number of files required to fully render the new page and the size of each such file, and network and server congestion and attendant delays occurring when the user activated the hotlink.

Interstitial web advertising is taught in, e.g., United States patents 5,737,619 and 5,572,643 (both of which issued to D. H. Judson but on April 7, 1998 and November 5, 1996, respectively -- hereinafter the

-10-

"Judson" patents). The Judson patents disclose the concept of embedding an advertisement, as an information object, in a web page file in such a manner that the object will remain hidden and not displayed when the file is executed to render the page. Rather than being displayed, the information object is locally cached by the browser during execution of the code for that page. Then, during a transition initiated by user activation of a hotlink to move from that page to a next successive page, i.e., during an interstitial, the browser accesses the advertisement from local cache and displays it until such time as that next successive page is downloaded and rendered. See also, published International patent application WO 97/07656 (to E. Barkat et al and published on March 6, 1997) which teaches the concept of "polite" downloading. Here, a browser, on a local computer (e.g., a client PC) downloads, from a remote advertising system server and ostensibly as a background process, file(s) for a web advertisement only during those intervals when bandwidth utilization of a communication channel (link) connected to the browser is less than a pre-established threshold. Such "polite" downloading is intended to minimally interfere with other communication applications, then executing on the client PC, which will utilize the link. The browser displays the downloaded ad(s) to the user only after the user has not interacted, as detected by a conventional screen saver process, with his(her) PC for a predefined period of time, such as by neither moving a mouse nor depressing a key on a keyboard during that period. The server selects those advertisements for download to the client PC based on a

-11-

user-ID and preference information of the user, who is then situated at that PC, and configuration information of that PC, which, when a connection is established between the client PC and the server, the client PC  
5 uploads to the server. Though the files associated with an interstitial advertisement can be large, these files are advantageously fetched by a client browser during those intervals when otherwise the browser would be idle and hence bandwidth utilization of its network connection  
10 would be relatively low. Such "idle times" would occur, in the absence of processing an interstitial ad, after the browser has fully rendered a web page and a user is viewing the page but has not yet clicked on a hotlink to transition to another page. During such an idle time,  
15 the browser would simply wait for further user input.

By reducing, if not eliminating, problems, inherent in banners and engendered by download latency, interstitial web advertisements, by employing idle time  
20 downloading and local caching, provide a theoretical promise of conveying very rich media content with a pleasing "user experience". However, interstitial advertisements, as conventionally implemented, have serious practical deficiencies which have severely  
25 limited their use.

Conventional interstitial, as well as other forms of current, web advertisements -- here not unlike banners -- rely on embedding HTML ad code, as, e.g., a  
30 separate non-displayable object, within HTML coding for a web page. Unfortunately, this approach, inherent in that

-12-

taught by the Judson patents, can be inflexible and expensive for an advertiser to implement and particularly later should that advertiser, for whatever reason, seek to modify his(her) ad content. In particular and  
5 presently, ad coding is manually inserted into each and every content web page that is to carry advertising. Consequently, insertion of increasingly sophisticated embedded advertising, such as multi-media or video or audio, in existing web site content requires a large  
10 investment in terms of human resources, time and cost as web sites, particularly large sites, increase a number of content pages available for advertising. In that regard, where a banner usually required insertion of, e.g., a single line of HTML code, content rich advertisements,  
15 such as those now implemented by parameterized embedded Java advertising applets, often consist of an entire page of coding and hence require far more extensive and increasingly labor-intensive and costly insertions. Moreover, over time, advertisers do change their ads --  
20 such as by replacing one ad with a totally new version. However, once HTML ad coding is embedded within a number of web pages, it can be quite impractical and rather costly for an advertiser to access each and every page in which his(her) ad coding has been inserted and then  
25 manually change the ad coding, as desired. The impracticality and attendant cost compound if these pages are copied to other web sites and hence diffuse through the Internet.

30                   Given these deficiencies, the art teaches a concept of implementing web advertising through using

-13-

so-called "push" technology. See, e.g., United States patent 5,740,549 (issued to J. P. Reilly et al on April 14, 1998 -- hereinafter the "Reilly et al" patent). In essence and as described in the Reilly et al patent, a

5 client PC, through execution of a "push" application program (called "administration manager"), establishes a network connection with an information server, i.e., a "push" web server, typically during off-hours, such as in the late evening or early morning, or at a predefined

10 interval (e.g., every four hours). The information server then downloads, i.e., "pushes", to the administration manager, content files, such as for advertisements and/or other predefined information, that are to be played to the user sometime later. The

15 administration manager, i.e., the "push" application, in turn, stores all the "pushed" content files into a local database (referred to as the "information database") on a local hard disk and, in response to instructions received from the information server, deletes those previously

20 "pushed" content files which have already been displayed. The administration manager also maintains a user profile, which specifies user preferences as to the specific advertising and/or other information (s)he wants to receive, in the information database. As such, through

25 each connection, the information server, by selecting content from its database relative to preferences specified in the user profile, attempts to "push" fresh content to the client PC that is likely to be of interest to the user but without duplicating that which was

30 already displayed. Stored "pushed" content is later displayed, using a data viewer, either on user demand or

-14-

during those times when the user is not interacting with the system, here too detected by a conventional screen saver procedure.

5                   While push technology reduces download latency, by shifting downloads to occur at off-hours, this technology also suffers serious drawbacks which have greatly restricted its practical acceptance.

10                   In particular, to access "pushed" content, a user must initially download and install to his(her) client PC a separate, platform-specific, software application program, as well as subsequent updates to that program as new push capabilities are released by the  
15                   manufacturer of the program. Unfortunately, these application programs can often extend to tens of megabytes in length. Since typical Internet users establish modem connections to their Internet service provider, these users will find that downloading these  
20                   relatively large program files, even in compressed form, will consume an inordinate amount of time and is generally impractical while (s)he is actively using his(her) client PC. Consequently, these users are constrained to purchasing, at some cost, an off-the-shelf  
25                   version of the application program or downloading that program, typically at no cost for the program itself, at off-hours, when network congestion is relatively light. Furthermore, while some efforts are underway in the art to automatically "push" and install incremental software  
30                   updates to a client PC, thus eliminating a need for a user to manually do so, the user still faces the burden

-15-

associated with the initial download and installation of the "push" application program.

In addition, "push" application programs  
5 continue to increase in size, often considerably, as they provide added capabilities to a user. Downloading and then regularly updating a push application will reduce, sometimes considerably, the amount of disk space available to the user on his(her) client PC.  
10 Furthermore, "push" applications rely on periodically "pushing" large quantities of media content from a push server to the client PC and storing that content on the hard disk of that PC pending subsequent display. This content, depending on its volume, can consume inordinate  
15 amounts of hard disk space. Furthermore, advertisers have discovered, not surprisingly, that relatively few PC users will undertake any affirmative action, such as by downloading and installing an application program -- almost regardless of its size, to receive advertisements  
20 and other such information.

Faced with these practical, and rather acute, deficiencies inhering in web advertising conventionally provided on either an interstitial or "push" basis, web  
25 advertisers have apparently relegated their efforts to displaying their advertisements on a banner-like approach, through real-time downloading and rendering of advertising HTML files. Here, the advertising files are sited on remote web servers, rather than being embedded  
30 within given web page HTML files, with appropriate HTML tags, which reference the ad files, being embedded into

-16-

the web page files themselves. Such a tag specifies when and where, within the page, an advertisement is to appear.

5                   To surmount the latency problems inherent in  
such banner-like advertisements, various proprietary  
media formats have appeared in the art. These formats  
employ increasingly sophisticated data compression,  
sometimes in conjunction with video and/or audio  
10   streaming. Rather than waiting for a media file to fully  
download prior to its being rendered, streaming permits  
content in a "streamed" media file to be presented in  
real-time to the user as that content arrives at his(her)  
client browser. While this approach clearly provides  
15   enhanced richness in content over that obtainable through  
a conventional banner and thus can heighten a "user  
experience", it nevertheless relies, to its detriment, on  
a continuous real-time network connection existing to a  
remote web server.

20                   Unfortunately, any network or server congestion  
which stops the download, even if temporary, can suspend,  
i.e., freeze, or totally halt the "streamed" media  
presentation to the user prior to its completion. This  
25   interruption, if noticeable and sufficiently long, will  
likely frustrate the user and degrade the "user  
experience".

30                   In spite of these drawbacks, particularly with  
respect to interstitial advertisements and push  
technology, and apparently for lack of a better

-17-

alternative, most web advertising currently in use employs real-time streaming of graphic files with their content being rendered by the browser.

5                Web advertisements, like other forms of mass advertising, do generate revenue, often in the form of an on-going stream of payments to the host of the ads, in this case web site owners. Accurate user accounting is essential to ensure that an advertiser is not over- or  
10 under-charged given an extent to which an ad is actually disseminated. Hence, these payments are often tied to a function of the number of web users whom the ad reached. But with web advertisements, accurately ascertaining that number has been difficult and problematic at best, and,  
15 given a basic technique employed to do so, manifestly error-prone, thereby causing unreliable user counts and erroneous ad charges.

              In particular and as conventionally employed,  
20 delivery of a web advertisement, such as, e.g., a streamed ad, is logged as a "user impression" at a web server at an instant an advertising file(s), e.g., a streamed file, is served, rather than after the browser has completely rendered the advertisement to the user.  
25 Unfortunately, serving these ad files does not guarantee that these files will be ultimately and completely rendered by a client browser to a user. Consequently, web server generated "user impression" counts can be grossly over- or under-stated. For example, if a user  
30 navigates to a new content page after an advertisement has started playing but before that advertisement

-18-

completes and, by doing so, prematurely terminated the advertisement, a full impression is nevertheless logged -- erroneously -- since that advertisement was completely served. Additional errors arise if a proxy server is

5 situated between multiple client PCs situated on an intranet or a local area network (LAN) and a web advertisement server situated on the Internet (or other insecure public network). In this case, a request from one of the client PCs for the advertisement files will be

10 routed to the proxy server, which, in turn, will direct that request onward to the advertisement web server. The latter, in response to the request, will serve one complete copy of the advertisement files to the proxy server. The resulting fetched advertisement files will

15 be locally cached in the proxy server and, from there, provided to the requesting client PC. Should any of the other client PCs request the same files, the proxy server will provide these files, totally unbeknownst to the web server, from its local cache rather than directing a

20 request from that other PC back to the web server. Hence, the web server will be totally oblivious to each additional instance in which the proxy server accessed the ad files from its local cache and disseminated the advertisement to any client PC other than that which

25 first requested the ad. Inasmuch as some intranets situated behind a proxy server(s) can be rather extensive with tens or hundreds of thousands of individual client PCs, server-based user impression accounting based on copies delivered by a web server may, owing to the

30 presence of proxy servers, be inordinately low and result in significant under-charges to the advertiser. As of

-19-

yet, no solution apparently exists in the art that can provide accurate counts of "user impressions" of web advertisements.

5                   Other conventional approaches aimed at reducing latency times associated with downloading content files through relatively slow speed communication links, e.g., modem connections, have involved development and use of new facilities within various programming languages.

10       These approaches, most notably involving the Java and JavaScript programming languages, while helpful, still cause inefficient use of available link bandwidth and still constrain the size of the content files. These limitations arise from premature terminations of

15       preloaded files whenever a user transitions to a new web page. Specifically, with these approaches, if a user activates a hotlink to transition to a new web page while an ad file is being downloaded but before the downloading has completed, then the downloading simply stops. The

20       downloading will need to be re-started, but from the beginning of the file, the next time that particular ad file is requested. Hence, the time and bandwidth that has then been expended in downloading part of that ad file is completely wasted. In practice, many users tend

25       to quickly navigate through a series of web pages until they reach a desired destination. Consequently, advertisers are constrained to again minimize content file sizes and hence "richness" of their advertisements in an effort to decrease a number of premature

30       terminations per unit time and in doing so reduce latency caused by downloading duplicate sections of the same ad

-20-

file. Therefore, these approaches have generally proven to be wholly unsatisfactory.

5 In view of the fundamental drawbacks associated with various web based advertising techniques known in the art, interstitial web advertising appears to hold the most promise of all these techniques. Yet, the limitations inherent in conventional implementations of conventional interstitial advertising have effectively  
10 prevented this form of web advertising from effectively fulfilling its promise. Moreover, the deficiencies inherent in all known web advertising techniques have, to a significant extent, collectively inhibited the use of web advertising in general.

15 Thus, a pressing need exists in the art for a new web-based interstitial advertising technique which does not suffer from infirmities associated with such interstitial advertising techniques known in the art.

20 In that regard, this new technique should preferably not embed advertising HTML files within a web page. If this could be accomplished, then advantageously such a technique would likely provide considerable  
25 economies to advertisers in saved labor, time and cost in terms of both inserting advertisements into web page files, and later changing any of those advertisements. In addition, such a new technique should preferably function in a manner that is substantially, if not  
30 totally, transparent to a user and which neither inconveniences nor burdens that user. In particular,

-21-

this new technique should preferably not require a user to download and install on his(her) PC a separate application program, let alone any update to it, specifically to receive web advertising, or perform any  
5 affirmative act, other than normal web browsing, to receive such advertising. Furthermore, this new technique should preferably be platform independent and, by doing so, operate with substantially any web browser on substantially any PC. Also, this new technique, when  
10 in use, should preferably not consume excessive hard disk space on a client PC. Moreover, to provide a pleasing "user experience", this new technique should render an ad fully and without any interruptions that might otherwise result from network and/or server congestion. Lastly,  
15 this new technique should provide proper accounting to an advertiser by accurately and validly ascertaining user impressions of fully rendered advertisements.

We believe that if such a new web-based  
20 interstitial advertising technique could be provided, then this technique, which should be both effective and desirable, may well achieve broad support and use by advertisers and acceptance by web users; hence, substantially expanding the use of web-based advertising  
25 in general.

#### SUMMARY OF THE INVENTION

Advantageously, our present inventive technique  
30 satisfies this need by overcoming the deficiencies

-22-

associated with conventional web-based interstitial advertising techniques.

Our present invention accomplishes this, in accordance with our broad inventive teachings, by: completely "decoupling" advertising content from a web content page (also hereinafter referred to as a "referring" page); "politely" downloading advertising files, through a browser executing at a client computer, into browser caches (e.g., browser disk and RAM cache) at that computer and in a manner that is transparent to a user situated at the browser; and interstitially displaying advertisements through the browser in response to a user click-stream associated with normal user navigation across different web pages.

Specifically, our technique relies on embedding an HTML tag (which, where necessary, to distinguish this tag from other HTML tags, will also be referred to hereinafter as an "advertising tag") into a referring page. This tag contains two components. One component effectively downloads, from a distribution HTTP (web) server and to an extent necessary, and then persistently instantiates an agent, implemented as a "light-weight" Java applet, at the client browser. This agent then "politely" and transparently downloads advertising files (media and, where necessary, player files), originating from an ad management system residing on a third-party advertising HTTP (web) server, for a given advertisement into browser disk cache (also in the case of media files into the browser RAM cache) and subsequently plays those

-23-

media files through the browser on an interstitial basis and in response to a user click-stream. The other component is a reference, in terms of a web address, of the advertising management system from which the  
5 advertising files are to be downloaded. This latter reference totally "decouples" advertising content from a web page such that a web page, rather than embedding actual advertising content within the page itself -- as conventionally occurs, merely includes an advertising tag  
10 that refers, via a URL, to a specific ad management system rather than to a particular advertisement or its content. The ad management system selects the given advertisement that is to be downloaded, rather than having that selection or its content being embedded in  
15 the web content page.

Advantageously, the agent operates independently, in the client browser, of the content in any referring web page. Once loaded and started, the  
20 agent executes in parallel, with standard browser functionality, continually and transparently requesting and downloading advertisements to browser cache residing in a client computer (e.g., personal computer -- PC) and interstitially playing those advertisements.

25  
In particular, once the agent is started, the agent politely and transparently downloads, through the client browser and to the browser cache, both media and player files, originating from the advertisement  
30 management server, for an advertisement that are needed to fully play content in that advertisement. The agent

-24-

also monitors a click-stream generated by a user who then operates the browser. In response to a user-initiated action, e.g., a mouse click, which instructs the client browser to transition to a next successive content web page and which signifies a start of an interstitial interval, the agent, if all the media and player files are then resident on the client hard disk, plays the media files, through the browser and during that interstitial interval, directly from the browser cache. Advertisements are interstitially played typically in the order in which they were downloaded to the client browser. Interstitial play from browser cache advantageously permits previously cached content rich advertisements to be played through the browser without adversely affecting communication link bandwidth then available to the client browser. Thus, the full available link bandwidth can be used, while an advertisement is being played, to download a next successive content web page.

Employing a user click-stream to trigger play of cached advertisements frees the user, for receiving advertising, of any need either to undertake any affirmative action, other than normal web browsing, or to learn any new procedure; thus, advantageously imposing no added burden on the user.

Advantageously, the agent "politely" downloads advertisement media and player files, originating from the advertising server, to the browser cache, during what otherwise would be browser idle times, i.e., while a web

-25-

page is being displayed to a user and the browser is waiting for user input. Caching advertisement files in this fashion advantageously circumvents variable latency and erratic (e.g., intermittent or suspended) play that frequently occurs with conventional streamed and static media delivered over the web.

At the start of an interstitial interval, the agent determines whether all the media and player files required to play a given advertisement (typically that having its so-called AdDescriptor file situated in a head of a play queue) then reside on the disk of the client PC or, with respect to media files, are resident in browser RAM cache. If so, the agent then accesses these files from the disk to "play" that advertisement. Since all the media and player files are then locally resident, the advertisement, from a user's perspective, is immediately rendered from the client hard disk or browser RAM cache with essentially no downloading delay, thus providing a highly pleasing "user experience" with rich multi-media content approaching that obtainable through current CD-ROM based delivery. Thereafter, the agent returns control to the browser to permit the browser, if a next successive web page has been downloaded, assembled and ready to be rendered, to render that particular page to the user. If, however, an advertisement is prematurely terminated by a user, that advertisement (in terms of its AdDescriptor file) will remain in a play queue (with its media and player files remaining on the client hard disk or, in the case of media files, in browser RAM cache) and will be re-played from its beginning at the start of a

-26-

next successive interstitial interval. Furthermore, if download of the media and player files for an advertisement were to be interrupted by a user click-stream, i.e., start of interstitial interval, the agent suspends further downloading until after the ensuing interstitial interval terminates. To conserve communication link bandwidth, the agent then resumes downloading of these files at a point it was suspended, rather than, as conventionally occurs, totally re-starting the download.

In accordance with our specific inventive teachings, the agent contains two applets: a Transition Sensor applet and an "AdController" applet. Only the Transition Sensor applet is itself associated with any content page. Though the AdController applet, once started, executes under the browser, it is not under the control of the browser itself.

The advertising tag is itself embedded in a content web page and references a JavaScript file. The advertising tag also encapsulates a reference, i.e., a URL to a specific ad management server, typically sited on a third party advertising server, containing specific media, that collectively constitutes web advertisements, and accompanying player files. The file, when executed, downloads and implements, through dynamic writing of applet tags, the Transition Sensor applet. This particular applet remains visually transparent to a user who displays, with his(her) browser, the HTML coding for that page. In particular, the advertising tag references

-27-

a JavaScript file (which contains a "script") stored on a distribution server. When the JavaScript file is downloaded and the script it contains is then executed by the browser, the script dynamically writes a predefined number and combination of applet tags, i.e., which collectively form the Transition Sensor applet, into the retrieved web page content in lieu of the advertising tag. Subsequent execution of these tags, by the client browser, invokes the Transition Sensor applet.

In particular, when executed, the Transition Sensor applet instantiates an Applet Registry, which is used for inter-applet communication. Thereafter, the Transition Sensor applet determines whether the AdController applet has been downloaded to the browser disk cache or whether an updated version of this particular applet resides on a distribution server. If an updated version of this applet exists on the distribution server relative to that previously downloaded to the browser disk cache or if this applet has not been download at all onto this cache, the Transition Sensor applet loads the AdController applet from the distribution server into the browser disk cache. The Transition Sensor applet then instantiates the AdController applet. Once this occurs, the Transition Sensor applet then establishes appropriate entries in the Applet Registry for itself and the AdController applet.

The Transition Sensor applet then passes the URL of the ad management system, as specified in the advertising tag, to the AdController applet in order for

-28-

the latter applet to request delivery of an advertisement, specifically an associated AdDescriptor file, originating from that system. The system then selects the advertisement to be delivered and, via the third party advertising server, so informs the AdController applet by returning the requested AdDescriptor file. For a given advertisement, this particular file, which is textual in nature, contains a manifest, i.e., a list, of: file names and corresponding web addresses of all media files that constitute content for that advertisement and all player files necessary to play all the media files; an order in which the various media files are to be played; and various configuration and other parameters need to configure and operate the operation of each player in order for it to properly play a corresponding media file(s). The AdController then "politely" downloads, typically via the advertising distribution server, the associated media and player files, as specified in the AdDescriptor file -- and to the extent they do not already reside on the hard disk of the client PC. As noted above, the Transition Sensor applet also monitors a click-stream produced by the current user to detect a user-initiated page transition and hence the start of an interstitial interval.

Advantageously, the AdDescriptor file implements a data abstraction that totally separates the media and player files from the referring web page thus assuring that the advertisement content itself remains completely independent of the content web page that invoked its presentation. This abstraction permits our

-29-

technique to provide a highly effective, generalized and very flexible mechanism for delivering rich web advertisements, particularly those that require complex sets of media files and players. Through use of this  
5 abstraction, our technique is able to handle present and future media formats, regardless of their requirements, including proprietary streaming and other content delivery technologies that rely on Java applets as a delivery mechanism -- all transparently to the user.  
10 Moreover, since the AdDescriptor file can specify media and player files for different browsers, operating systems and computing platforms then in use, our technique can readily function with a wide variety of different computing and browsing platforms.

15  
The Transition Sensor and AdController applets are each implemented through appropriate Java classes and collectively persist, through storage in the browser disk cache, across different content pages within a site,  
20 across different web sites, and across successive browser sessions. Once either of these applets is completely downloaded, providing it is not subsequently flushed from the browser disk cache as the user navigates across web sites on the web, the files for that applet will be  
25 loaded from that cache, rather than being downloaded from the distribution server, the next time that applet is required, e.g., when the user next navigates, either during a current browser session or a subsequent session, to any content page that contains an advertising tag.

-30-

Whenever the client browser encounters a next successive page containing an advertising tag, then the browser will first and automatically inquire with the distribution server to ensure that executable code for the Transition Sensor applet, if previously downloaded into the browser disk cache, has not been superseded by an updated version. If such an updated version then exists, the browser will collectively download updated files from the distribution server and replace, to the extent necessary, each Transition Sensor applet file residing in the browser disk cache with its updated version. Alternatively, if the Transition Sensor applet has not been previously downloaded into the browser disk cache, then the browser will download all the necessary files for the Transition Sensor applet from the distribution server into that cache. The Transition Sensor applet, once executing, will load, through the browser, the AdController applet. To do so, the browser will, if necessary, obtain an updated version, from the distribution server, in the same manner as it did for the Transition Sensor. As a result, any corrections or enhancements made to the agent (specifically the Transition Sensor and/or the AdController applets) since the agent was last downloaded to the client browser will be automatically and transparently, from a user perspective, distributed to that browser and downloaded into the browser disk cache the next time the browser encounters a web page containing an advertising tag. By operating in this fashion, the user is totally and advantageously relieved of any need to: both initially

-31-

load and install an application program to obtain advertising and/or later update that program.

Furthermore, the agent advantageously persists  
5 and functions transparently in background, independent  
and transparent to user navigation across pages on a  
common web site and across web sites. The agent  
effectively implements a background process which runs in  
parallel with and is transparent to normal HTML and HTTP  
10 operations implemented by the client browser.

Moreover, in sharp contrast to conventional  
server-based accounting of web advertisements, our  
inventive technique provides highly accurate client-side  
15 accounting of each user impression. Each log entry,  
produced by the AdController applet, specifies a  
successful presentation of a complete advertisement at a  
client browser. This entry may include a source of the  
ad content, i.e., in terms of the URL of the associated  
20 ad management system, a title of the advertisement and  
the URL of the referring web page. Other client-side  
information can be measured and included in each entry,  
such as: an amount of time during which the advertisement  
was rendered by the browser (presumably during which the  
25 user dwelled on the advertisement); as well as an  
identification, in terms of a URL, of a content web page  
to which the user next navigated (particularly if the  
user reached that page through a hotlink displayed in the  
advertisement). Subsequently, the AdController applet  
30 uploads the log entries to the advertising server. These  
entries will be collectively processed, as needed, to

-32-

permit shared ad revenues from web-based advertisers to be properly allocated among different web page content providers.

5                    Advantageously, our inventive technique, by  
totally decoupling referring web page content from its  
corresponding advertising content, easily permits an  
advertiser to change or update any of its advertisements  
by just modifying, as needed, appropriate media and  
10    AdDescriptor files that reside in the third-party  
advertising management system. Since a referring web  
page merely incorporates an advertising tag totally  
devoid of advertising content, no changes whatsoever need  
to be made to that page. Hence, use of our inventive  
15    technique substantially reduces the burden, time and cost  
associated with maintaining and updating web-based  
advertising over that conventionally required.

                  As a feature, our inventive technique  
20    advantageously implements, in conjunction with its  
persistent agent approach, multi-threaded pipelining. By  
processing each different advertisement as a different  
thread, each one of a sequence of different processing  
operations can be performed, effectively on a pipe-lined  
25    parallel basis, on different sequentially occurring  
advertisements, thereby enhancing a rate (increasing  
throughput) at which advertisements can be queued for  
playback. In addition, through such pipe-lining, logging  
of a fully presented advertisement can occur as a last  
30    operation in a pipeline and essentially in parallel  
either with: presentation of cached advertisement having

-33-

its AdDescriptor file situated in the play queue immediately behind that for the just presented advertisement, or downloading and caching of a next successive advertisement.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

10

FIG. 1A depicts the correct alignment of the drawing sheets for FIGs. 1B and 1C;

15

FIGs. 1B and 1C collectively depict a high-level block diagram of an illustrative client-server distributed processing environment, implemented through the Internet, which embodies the teachings of our present invention, along with, as pertinent to the invention, basic inter-computer actions that occur in that environment and associated client processing operations;

20

FIG. 1D depicts the correct alignment of the drawing sheets for FIGs. 1E and 1F;

25

FIGs. 1E and 1F collectively depict the same environment as shown in FIGs. 1B and 1C but showing a detailed version of agent download/instantiate/execute operations 50 shown in the latter figures;

30

-34-

FIG. 2 depicts the correct alignment of the drawing sheets for FIGs. 2A and 2B;

5        FIGs. 2A and 2B collectively depict generalized web page HTML code 35, specifically inclusion of advertising tag 40, which transparently invokes our invention, and changes which our invention dynamically makes to that code, specifically substitution of Transition Sensor applet 210 for tag 40 to yield  
10        page 35', in order to download and render web advertisements;

15        FIG. 3 depicts a high-level block diagram of client PC 5 shown in FIGs. 1B and 1C, and 1E and 1F;

FIG. 4 depicts a simplified high-level block diagram of application programs 400 resident within client PC 5 shown in FIG. 3;

20        FIG. 5 depicts a high-level block diagram of AdController agent 420 shown in FIG. 4, which implements our present invention;

25        FIG. 6 depicts the correct alignment of the drawing sheets for FIGs. 6A and 6B;

FIGs. 6A and 6B collectively depict a high-level flowchart of processing operations 600 performed by AdController agent 420 shown in FIG. 5;

-35-

FIG. 7 depicts a high-level block diagram of basic processing threads that implement AdController applet 424 which, as shown in FIG. 4, forms part of AdController agent 420;

5

FIG. 8 depicts a high-level flowchart of processing operations 800 performed by AdController applet 424 shown in FIG. 7;

10

FIG. 9 depicts the correct alignment of the drawing sheets for FIGs. 9A and 9B;

FIGs. 9A and 9B collectively depict a flowchart of processing operations 900 performed by AdController applet 424, shown in FIG. 7, specifically for processing an advertisement;

15

FIG. 10 depicts inter-applet events that occur within AdController agent 420 during execution of Transition Sensor applet 422;

20

FIG. 11 depicts a high-level block diagram of basic processing threads that implement Transition Sensor applet 422 which, as shown in FIG. 4, forms part of AdController agent 420;

25

FIG. 12 depicts a high-level flowchart of processing operations 1200 performed by Transition Sensor applet 422 shown in FIG. 11;

-36-

FIG. 13 depicts a high-level block diagram of Ad Loader process 1300 which can be used to provide advertiser control over various functions, for advertisement play and logging, implemented by AdController applet 424;

FIG. 14 depicts a high-level block diagram of Ad Pipeline 545 that is implemented by and forms part of AdController applet 424 shown in FIG. 4;

FIG. 15 depicts a high-level block diagram of Ad Producer process 1500 that is executed by Ad Pipeline 545 shown in FIG. 14;

FIG. 16 depicts a high-level block diagram of Ad Location process 1600 that is also executed by Ad Pipeline 545 shown in FIG. 14;

FIG. 17 depicts a high-level block diagram of Ad Downloader process 1700 that is also executed by Ad Pipeline 545 shown in FIG. 14;

FIG. 18 depicts a flowchart of stop method 1800 invoked by Transition Sensor applet 422 shown in FIG. 4;

FIG. 19 depicts a flowchart of start method 1900 invoked by Transition Sensor applet 422 shown in FIG. 4; and

FIG. 20 depicts contents of actual illustrative AdDescriptor file 2000 for use in interstitially

-37-

rendering a PointCast type Java advertisement through our present invention.

5 To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

#### DETAILED DESCRIPTION

10

After considering the following description, those skilled in the art will clearly realize that the teachings of our present invention can be utilized in any networked client-server environment in which advertising or other information is to be presented to a user during interstitial intervals, i.e., during a transition between successively displayed web pages. Such an environment can encompass the Internet or an intranet, or any client-server environment in which a client browser (regardless of whether that browser executes on a dedicated client computer or not) is used to access and download web pages or, more generally speaking, files through a network communication channel (link) from a server (again regardless of whether that server executes on a dedicated computer or not). In that regard, the server can be a separate software application which executes on any computer in the networked environment, even if that computer is itself a client to another server in the network.

-38-

For purposes of simplicity and to facilitate reader understanding, we will discuss our present invention in the illustrative context of use in rendering interstitial web-based advertisements to a client  
5 personal computer (PC) connected to the Internet, where specifically a client browser executing in the PC is used to download and render web pages from a remote networked Internet accessible web server. Clearly, after  
10 considering the ensuing description, anyone skilled in the art will readily appreciate how the teachings of our invention can be easily incorporated into any client-server or other similar distributed processing environment in which a client can encompass not only a specific computer connected to a network but a software  
15 process that possesses network connectivity to another such process and requests information from and, in response, obtains information supplied by the latter.

We will first present an overview of our  
20 invention, particularly in the context of its use with an Internet web browser in a client PC, followed by describing each basic component of its implementation.

#### 25 A. Overview

A general deployment of our invention in an Internet environment is collectively shown in FIGs. 1B and 1C, with a detailed view of a portion of the inter-processor agent download/instantiation  
30 operations 50 shown in these figures being depicted in FIGs. 1E and 1F. The correct alignment of the drawing

-39-

5 sheets for FIGs. 1B and 1C, and 1E and 1F is shown in  
FIGs. 1A and 1D, respectively. FIGs. 2A and 2B, for  
which the correct alignment of the drawing sheets for  
these figures is shown in FIG. 2, collectively depicts  
generalized web page HTML code which transparently  
invokes our invention, and changes which our invention  
dynamically makes to that code in order to download and  
render web advertisements. For a understanding, the  
reader should simultaneously refer to FIGs. 1B and 1C, 1E  
10 and 1F, and 2A and 2B throughout the following  
discussion.

As shown, client PC 5, upon which client  
browser 7 executes, is connected through communication  
15 link 9 to Internet 10. Browser 7 is a conventional web  
browser, such as Internet Explorer or Netscape Navigator  
commercially available from Microsoft Corporation or  
Netscape Corporation, respectively. Preferably, for  
reasons that will shortly become clear, that browser  
20 should preferably support dynamic writing of applet tags.  
Though, for ease of illustrating inter-computer actions,  
we depicted Internet 10 as having portions 10<sub>A</sub> and 10<sub>B</sub>, we  
will collectively refer to both portions as simply  
Internet 10. Web server 13, connected, via link 11, to  
25 Internet 10 represents any web HTTP (hypertext transfer  
protocol) server. This server, in response to a request  
to fetch a specific file from web browser 7, downloads  
that file, using conventional TCP/IP protocols  
(transmission control protocols/internet protocols),  
30 through the Internet to browser 7. Browser 7 will, in

-40-

turn, render that file typically on a monitor to a user situated at the client PC.

Advertising distribution HTTP server (also referred to as "agent" server) 15 is connected, via communications link 17, to Internet 10 and stores files that collectively implement a predefined agent, specifically, a light weight Java applet. This agent (referred to herein as the "AdController" agent) transparently pre-loads itself, as well as media rich advertising content, into a local hard disk cache associated with the browser ("browser disk cache") on client PC 5. Server 15 downloads the AdController agent in a manner to be described below, to client browser 7. This agent, once instantiated and started, then transparently and politely downloads (actually pre-loads) advertisements into the browser disk cache, and subsequently plays each of those advertisements, on an interstitial basis, in response to a click stream generated by the user as (s)he navigates, through use of browser 7, between successive web pages. Such hard disk caching advantageously circumvents variable latency and erratic play associated with conventional streamed and static media delivered over the Internet. The agent enables rich advertising to be presented in a highly-controlled fashion, resulting in user experiences approaching that of CD-ROM.

Third-party ad HTTP server 20, connected to Internet 10 via, e.g., communications links 18 and 23, hosts ad management system 25. In essence and as

-41-

discussed in detail below, this system, in response to a request originating from the AdController agent executing in browser 7, selects a given advertisement and then downloads, in a "polite" manner controlled by the agent, media and player files that form that advertisement to the agent for storage in the browser disk cache. Inasmuch as Java applets are currently restricted under constraints inherent in the Java programming language itself to retrieving files from an identical Internet host that served the applet itself, the request for an advertisement to system 25 as well as resulting media and player files served by system 25 are routed through agent server 15 as a proxy server.

Advantageously, our inventive technique completely "decouples" advertising content from a web content page (also hereinafter referred to as a "referring" page). This, in turn, permits our technique to render media-rich advertisements without requiring inclusion of any advertising content into a referring web page. This "decoupling" is effectuated through inclusion of an HTML tag into a content web page, which when the latter is downloaded, interpreted and executed by the browser, effectively loads and instantiates the agent and then retrieves advertisement files from an ad management system specified in the tag. Thus, advertising files (both media and player files) can be maintained totally independently of their referring web page(s), with advantageously any changes made to the former having no effect on HTML coding contained in the latter.

-42-

In particular, HTML tag 40 (which, where necessary, to distinguish this tag from other HTML tags, will also be referred to hereinafter as an "advertising tag") is embedded by a content provider(s) into HTML code that constitutes each referring web page, e.g., here page 35. Generally, the position of this tag relative to existing HTML code (shown as HTML code portions 35<sub>A</sub> and 35<sub>B</sub> in FIGs. 2A and 2B) for this page is not critical. Advantageously, very rarely, if ever at all, do any changes need to be made to these code portions to accommodate the tag. As shown and as reproduced in Table 1 below, this tag, which typically consumes one line in a web page, implements a script.

```
<SCRIPT SRC=http://unicast.com/loadad.js>  
AdServer="http://AdManagement system"  
</SCRIPT>
```

TABLE 1 -- ADVERTISING TAG

One portion of the advertising tag ("SRC=http://unicast.com/loadad.js"), when executed by the browser, downloads a JavaScript file (named "loadad.js") from the agent server. This file, in turn, is then interpreted and executed, as a script, by the browser. The effect of executing this script, as symbolized by block 200 shown in FIGs. 2A and 2B, is to substitute applet tags, dynamically written by the script, into the referring web page in lieu of advertising tag 40 so as to form a modified web page, here referring content page 35', residing in the browser

-43-

disk cache. The script, by invoking a feature associated with dynamic writing, completely hides these tags from view should the user then display HTML source code for page 35' with his browser. This, in turn, hinders the user, to a certain degree, from readily ascertaining the source of the agent and ad management systems.

Collectively, these applet tags form Transition Sensor applet 210. This script, as described in detail below and is reproduced in Table 2 below, when interpreted and executed by a Java virtual machine (Java interpreter) resident in the browser persistently loads and then instantiates the Transition Sensor itself which, in turn, loads and instantiates the remainder of the agent in the client browser.

```
<applet code="com.unicast.adcontroller.tools.TransitionSensor"
codebase="http://www.unicast.com/java/classes/"
align="baseline" width="0" height="0" name="TransitionSensor"
archive="adcontroller.jar">
<param name="adURL"
value="http://www.unicast.com/media/fireworks_01_ad_descriptor.txt">
<param name="cabbase" value="adcontroller.cab">
</applet>
```

TABLE 2 -- TRANSITION SENSOR APPLET

The value of attribute CODE in the Transition Sensor applet specifies a Java executable that will be executed by the client browser, when it renders this applet, to launch the Transition Sensor. The executable, implemented through an appropriate Java class, was originally compiled from its associated Java source code file. Tags labeled "<WIDTH>" and "<HEIGHT>" jointly

-44-

specify a rectangular portion of a web page, as displayed by browser 7, in which the applet will be rendered. Since, here that portion is non-existent, nothing will be rendered. Applets, such as this one, can be delivered  
5 transparently over the Internet to the client PC and require no user-assisted installation.

Another portion of the advertising tag ("AdServer="http://AdManagement\_system") references a URL  
10 of a particular ad management system (where "AdManagement\_system" represents a web address (URL) of that particular system), here illustratively system 25, from which the agent is to download an advertisement. As will be seen below, the Transition Sensor applet, during  
15 its execution, passes this URL, as part of an advertising download request, to the remainder of the AdController agent to subsequently download appropriate advertising files, also as described below, from that system necessary to interstitially play an advertisement.

20 If advertisements are to play on client browsers (specifically Microsoft Internet Explorer version 3) that do not support dynamic writing of applet tags, then applet 210 would need to be inserted by  
25 content providers into each referring web page in lieu of advertising tag 40. Unfortunately, Transition Sensor applet 210 identifies both the agent server, and an actual advertisement in terms of a URL of its source components (through contents of an "AdDescriptor" file --  
30 which will be discussed in detail below -- specified in this applet). Since browser technology continues to

-45-

rapidly advance with most users continually upgrading their browsers, most browsers now in use, and in a very short time nearly all such browsers, will support such dynamic writing. Hence, we see little, and very shortly  
5 essentially no need, to embed applet 210 into any referring web pages, thus minimizing ad insertion cost, effort and time while restricting disclosure of the agent server and advertisement source information.

10               The agent, during its execution, "politely" and transparently downloads advertising files (media, and where necessary player files), originating from ad management system 25 for a given advertisement into browser disk cache (with the media files also being  
15 written into browser RAM cache) and subsequently plays those media files through the browser on an interstitial basis and in response to the user click-stream.

Advantageously, the agent operates  
20 independently, in the client browser, of the content in any referring web page. Once loaded and started, the agent executes in parallel, with standard browser functionality, continually and transparently requesting and downloading advertisements to a browser disk cache  
25 residing on a local hard disk ("browser disk cache"), as well as in the case of media files into browser RAM cache, in a client computer (e.g., personal computer -- PC) and interstitially playing those advertisements.

30               Now, with the above in mind and specific reference to FIGs. 1B and 1C, we will now describe the

-46-

basic inter-computer actions associated with use of our invention, as well as the basic attendant processing steps that occur in the client PC.

5                   To begin a browsing session, the user first  
invokes client browser 7. Once the browser is executing,  
the browser obtains, as an initial web page -- selection  
of this page being referenced by numeral 31, an address  
either of a prior so-called "default" content page  
10                   previously specified by the user and having its URL  
stored in the browser or of a content page manually  
entered by the user. The client browser then issues, as  
symbolized by block 33, a request to fetch a file for  
that page; with the request containing a URL of that page  
15                   (i.e., its complete web address including its file name).  
We assume for simplicity that the file for that page  
resides on web server 13. We also assume that page 35 is  
being requested which will invoke an associated  
interstitial advertisement in accordance with our  
20                   invention. In response to the request routed to  
server 13 -- as symbolized by line 34, this particular  
server downloads, as symbolized by line 36, to client  
PC 5 a file for page 35, where the coding stored in this  
file contains advertisement tag 40. Illustrative  
25                   contents of this tag are shown in dashed block 45, as  
well as in FIGs. 2A and 2B.

                  Once this file is received as shown in FIGs. 1B  
and 1C, browser 7 interprets and then executes, as  
30                   symbolized by block 52, the HTML code in page 35, which  
includes tag 40 and thus undertakes the actions shown in

-47-

agent download/instantiate/execute operations 50. These operations eventually result in the AdController agent being downloaded, instantiated and started in the client browser. Generally speaking, the browser in response to  
5 executing the advertising tag, issues a request, as symbolized by line 54, to agent server 15 to download the AdController agent. Through various inter-processing operations, as shown in further detail in FIGs. 1E and 1F and which will be described below shortly, server 15  
10 accesses and downloads, as symbolized by line 56, the needed files to install the AdController agent to execute under browser 7 on the client PC. Once files for the agent are downloaded to the browser disk cache on the client PC, the browser then instantiates and starts the  
15 agent executing, as symbolized by block 58. Operations 50 effectively conclude once the agent begins executing.

Now referring to operations 50 as shown in  
20 further detail in FIGs. 1E and 1F, upon entry into these operations, browser 7 executes, as symbolized by block 110, advertising tag 40. The browser then issues a request, as symbolized by line 115, to agent server 15, to download a JavaScript file (named, e.g., "loadad.js")  
25 specified in the request. This file is specified as the first portion of the advertising tag. In response to this request, server 15 downloads, as symbolized by line 120, this particular file onto browser 7 where that file is cached appropriately. Once the file is fully  
30 downloaded, it is interpreted and executed by a Java virtual machine (a Java interpreter integrated into the

-48-

browser and which generates code compatible with and executable by the browser). As indicated by block 125, the browser then executes the interpreted code for the script which, in turn, dynamically writes applet tags --  
5 in the manner generally shown in FIGs. 2A and 2B and described above -- into web page 35 in lieu of the advertising tag. These tags, which collectively form Transition Sensor applet 210, include a reference to a specific ad management system as specified in the second  
10 portion of advertising tag 40.

Once these tags are dynamically written into content web page 35 (to yield modified version 35' shown in FIGs. 2A and 2B), Transition Sensor applet 210 is  
15 instantiated and then executed. In particular, browser 7 determines whether executable code for the Transition Sensor applet has been previously downloaded to the browser disk cache. If this code has not been downloaded or an updated version of this code exists on agent  
20 server 15, the browser issues, as symbolized by line 130, a request to download a latest version of the Transition Sensor executable code from the agent server. Server 15, in response to this request, downloads, as symbolized by line 135, file(s) for the latest version of the  
25 transition sensor code to the browser which, in turn, stores these file(s) into the browser disk cache. Thereafter as symbolized by block 140, the browser instantiates and starts execution of the Transition Sensor applet. This latter applet, as part of its  
30 initial execution, instantiates an Applet Registry. This registry provides a mechanism, within the agent, for

-49-

inter-applet communication between the constituent Transition Sensor and AdController applets.

5        Thereafter, the Transition Sensor applet attempts to load, also as symbolized by block 140, the AdController applet, through the browser, from the browser disk cache. To do so, the browser first determines whether the AdController applet has been downloaded to the browser disk cache or whether an  
10        updated version of this particular applet resides on agent server 15. If an updated version of this applet exists on the agent server relative to that previously downloaded to the browser disk cache or if the AdController applet has not been download at all into  
15        this cache, the browser issues a request, as symbolized by line 150, to download a latest version of the AdController applet from agent server 15. Server 15, in response to this request, downloads, as symbolized by line 155, file(s) for the latest version of the  
20        AdController applet to the client browser which, in turn, stores these file(s) into the browser disk cache. Lastly, as symbolized by block 160, the Transition Sensor applet then instantiates and starts the AdController applet; and thereafter establishes appropriate entries in  
25        the Applet Registry for itself and the AdController applet.

30        Returning to FIGs. 1B and 1C, once operations 50 have completed, such that the agent is executing under browser 7, the AdController applet issues, as symbolized by block 60, a request, via agent

-50-

server 15, to download an AdDescriptor file from the ad management system, e.g., ad management system 25, specified in advertising tag 40. This request contains the URL of the ad management system contained in advertising tag 40. Currently, Java applets are restricted under constraints inherent in the Java programming language itself to retrieving files from an identical Internet host that served the applet itself. As such, rather than directing this request to advertising server 20, on which ad management system 25 resides, this request, as symbolized by line 62, is addressed to agent server 15, which serves as a proxy server between client PC 5 and advertising server 20. Both the request and resulting advertising (including media and player) files will be served to the client PC through agent server 15. As such, once the request has been received by the agent server, this server passes the request onward, as symbolized by line 64, to advertising server 20.

20

In response to this request for an AdDescriptor file, ad management system 25 then selects a specific advertisement to be delivered to client PC 5. This selection can be selected on a predefined or random basis, or based on user preference or other user-specific information previously collected from and associated with the user then operating browser 7. Such user-specific information, such as prior buying patterns, could have been appropriately pre-collected at the client PC, previously uploaded to ad management system 25 and processed there such that, upon receipt of the

30

-51-

AdDescriptor request, system 25 would then select and download an appropriate advertisement specifically targeted to the user then situated at the client PC. In any event, once system 25 selects the advertisement, through whatever selection metric it employs, the corresponding AdDescriptor file is then downloaded, as symbolized by line 66, to agent server 15 (here being a proxy server) which, in turn, as symbolized by line 68, supplies that file to the AdController agent then executing under web browser 7.

To digress slightly, for the selected advertisement, the AdDescriptor file is a text file that contains a manifest, i.e., a list, of file names and corresponding network locations (URLs) at which these files reside, and player instructions and configuration parameter values necessary to play the entire advertisement through web browser 7 to the user. FIG. 20 shows contents of typical AdDescriptor file 2000 for a PointCast Java advertisement. Specifically and as shown in section 4C of file 2000, this AdDescriptor file lists file names with partial addresses on the ad management system of all media files that constitute content for that advertisement, and, in section 1 of this file, all Java player files necessary to play all the media files. This file also respectively specifies, here shown in sections 3 and 4B, an order in which the various media files are to be played, and various configuration parameters needed to properly configure the operation of each player to play each corresponding media file.

-52-

5       The AdDescriptor file implements a data  
abstraction that totally separates the media and player  
files from the referring web page, here page 35, thus  
assuring that the advertisement content itself remains  
completely independent of the content web page that  
invoked its presentation. This abstraction permits our  
technique to provide a highly effective, generalized and  
very flexible mechanism for delivering rich web  
advertisements, particularly those that require complex  
10       sets of media files and players. Through use of this  
abstraction, our inventive technique can handle present  
and future media formats, regardless of their  
requirements, including proprietary streaming and other  
content delivery technologies that rely on Java applets  
15       as a delivery mechanism -- all transparently to the user.  
Moreover, the AdDescriptor file can contain separate  
listings (though not contained in file 2000 shown in  
FIG. 20) that delineate media and player files for  
different browsers, client operating systems or computing  
20       platforms (to the extent any of these require different  
versions of the media and/or player files) then in use.  
As such, our technique can readily function with a wide  
variety of different client computers and browsing  
platforms.

25

      Once the AdDescriptor file is downloaded to the  
client PC, via agent server 15, the AdController then  
"politely" downloads, as symbolized by block 70 shown in  
FIGs. 1B and 1C, into the browser disk cache each media  
30       and player file, as specified in the AdDescriptor file --  
to the extent that file does not already reside on the

-53-

hard disk of the client PC. Through so-called "polite" downloading, media and player files are downloaded to browser 7 during browser idle time intervals, with the downloading suspended during each ensuing interstitial interval after the user instructs browser 7 to navigate to a new content web page. In this manner, while a fully downloaded advertisement is interstitially played from browser cache, the new content page is downloaded over the full bandwidth of communications link 9.

Advantageously, the communications link is freed during each interstitial interval to just carry web page content, thereby expediting download of content pages. If, due to the occurrence of an interstitial interval, the AdController applet suspends downloading of an advertisement file, then upon termination of this interval, this applet then resumes downloading at a location in that file at which downloading had stopped, thus conserving communication bandwidth and reducing download time.

20

In particular, as part of the operations symbolized by block 70, the AdController applet determines which files, of those listed on the AdDescriptor, do not then reside on the hard disk of client PC 5. Once it has made that determination, this applet issues a request, as symbolized by line 72, to agent server 15, to fetch a first one of these files. The agent server, again serving as a proxy server, issues a request, as symbolized by line 74, to fetch this file from a networked server, anywhere on Internet 10, on which that file resides. For simplicity, we assume that

30

-54-

all such files reside on server 20 and are accessible through ad management system 25. Hence, system 25, via server 20, issues a response, as symbolized by line 76 to agent server 15, containing this first advertisement file. The agent server, in turn and as symbolized by line 78, downloads this particular file to client browser 7 for storage in the browser disk cache. Downloading of advertisement files continues in this manner until, as symbolized by line 88, a last required file for the advertisement has been downloaded, via agent server 15, to the browser disk cache on client PC 5.

As the advertisement files for a common advertisement are being downloaded, the Transition Sensor applet also monitors, as symbolized in block 90, a click-stream produced by the current user so as to detect a user-initiated page transition. Once such a transition occurs, usually caused by a user engendered mouse click, and hence an interstitial interval starts, the AdController applet plays, also as symbolized by block 90, a fully cached advertisement (assuming all its media and player files have been downloaded) in the manner specified in its associated AdDescriptor file and using the players specified therein. Also, at the inception of the interstitial interval, the browser issues, also as symbolized by block 90, a request to fetch the next successive web page to which the user desires to transition. Once the advertisement has fully played, or until the next successive content web page is fully downloaded and assembled, or a user has closed an advertisement window, whichever occurs first (assuming

-55-

the AdDescriptor file specifies that the advertisement can be prematurely terminated), then control is returned, as symbolized by path 94, to the client browser to await completion of the download and interpretation of HTML  
5 code that forms that next content page and subsequent execution, of an advertising tag therein to invoke agent download/instantiate/execute operations 50 for that page; and so forth.

10           The Transition Sensor and AdController applets are each implemented through appropriate Java classes and collectively persist, through storage in the browser disk cache, across different content pages within a site, different web sites, and successive browser sessions.  
15 Once either of these applets is completely downloaded through operations 50, providing that applet is not subsequently flushed from the browser disk cache as the user navigates across web sites on the web, the files for that applet will be loaded from that cache, rather than  
20 being downloaded from agent server 15, the next time that applet is required, e.g., when the user next navigates, either during a current browser session or a subsequent session, to any successive content page that contains advertising tag 40.

25           Whenever client browser 7 encounters a next successive content page containing advertising tag 40, then the browser, will first and automatically inquire with agent server 15 to ensure that executable code for  
30 the Transition Sensor applet, if previously downloaded into the browser disk cache, has not been superseded by

-56-

an updated version. If such an updated version then exists, the browser will collectively download updated files from the agent server and replace, to the extent necessary, each Transition Sensor applet file residing in the browser disk cache with its updated version. Alternatively, if the Transition Sensor applet has not been previously downloaded into the browser disk cache, then the browser will download all the necessary files for the Transition Sensor applet from the agent server into that cache. The Transition Sensor applet, once executing, will load, through the browser, the AdController applet. To do so, the browser will, if necessary, obtain an updated version, from the agent server, in the same manner as it did for the Transition Sensor. As a result, any corrections or enhancements made to the agent (specifically the Transition Sensor and/or the AdController applets) since the agent was last downloaded to the client browser will be automatically and transparently, from a user perspective, distributed to that browser and downloaded into that disk cache the next time the browser encounters a web page containing an advertising tag. By operating in this fashion, the user is totally and advantageously relieved of any need to: both initially load and install an application program to obtain advertising and/or later update that program.

Specifically, cross page persistency of the Transition Sensor agent is accomplished by using a Java "singleton" design. A singleton design allows only a single object to ever be created and is accomplished by declaring a Java class as static. Since all applets run

-57-

in a same instance of a Java virtual machine, therefore all applets and their associated code share all static class variables. A static Applet Registry class is instantiated automatically by the Transition Sensor applet at its run time and, by implementing the Applet Registry, provides all inter-applet communication between the Transition Sensor and the AdController applets and their threads. The Applet Registry class implements a "loadAdController" method which, in turn, instantiates the persistent AdController applet. Through this method, the Transition Sensor applet downloads the AdController applet only if the latter applet has either been updated, relative to that version of this applet then resident in the browser disk cache, or does not then reside on the browser disk cache. The AdController applet then instantiates all its own threads that collectively implement transparent advertisement downloading and play mechanisms.

20           The AdController applet is itself created by an Applet Registry singleton object and creates all other objects that collectively constitute a run time agent execution module. This applet extends standard applet class definitions by over-riding standard Java applet  
25   init (initialize), start, run, stop and destroy life cycle methods, conventionally implemented in the client browser, with corresponding substitute methods. The substitute stop method ensures that a traditional response provided by the browser of halting execution for  
30   either the AdController applet does not occur whenever the browser calls the stop method to terminate the

-58-

lifecycle of this applet; hence, advantageously providing persistence to the agent across successive content pages. Consequently, the agent continues executing until the user terminates execution of (closes) the browser itself.

5

Thus, the agent persists and functions transparently in background, independent and transparent to user navigation across pages on a common web site and across web sites. In that regard, the agent effectively implements a background process which runs in parallel with and is transparent to normal HTML and HTTP operations implemented by the client browser.

To significantly simplify the description and the accompanying drawings, we have intentionally omitted from this discussion specific Java classes that constitute the AdController agent as well as, to increase a rate at which advertisements can be queued for playback, an accompanying software architecture for processing these classes on a multi-threaded pipelined basis. Such details are conventional in nature; hence, their use in implementing our present invention would be readily apparent to any one skilled in the art.

25 B. Client PC

FIG. 3 depicts a block diagram of client PC 5.

As shown, the client PC comprises input interfaces (I/F) 320, processor 340, communications interface 350, memory 330 and output interfaces 360, all

30

-59-

conventionally interconnected by bus 370. Memory 330, which generally includes different modalities, including illustratively random access memory (RAM) 332 for temporary data and instruction store, diskette drive(s) 334 for exchanging information, as per user command, with floppy diskettes, and non-volatile mass store 335 that is implemented through a hard disk, typically magnetic in nature. Mass store 335 may also contain a CD-ROM or other optical media reader (not specifically shown) (or writer) to read information from (and write information onto) suitable optical storage media. The mass store stores operating system (O/S) 337 and application programs 400; the latter illustratively containing browser 7 (see, e.g., FIGs. 1B and 1C) which implements our inventive technique. O/S 337, shown in FIG. 3, may be implemented by any conventional operating system, such as the WINDOWS NT, WINDOWS 95, or WINDOWS 98 operating system ("WINDOWS NT", "WINDOWS 95" and "WINDOWS 98" are trademarks of Microsoft Corporation of Redmond, Washington). Given that, we will not discuss any components of O/S 337 as they are all irrelevant. Suffice it to say, that the browser, being one of application programs 400, executes under control of the O/S.

Incoming information can arise from two illustrative external sources: network supplied information, e.g., from the Internet and/or other networked facility, through communication link 9 to communications interface 350, or from a dedicated input source, via path(es) 310, to input interfaces 320.

-60-

Dedicated input can originate from a wide variety of sources, e.g., an external database. In addition, input information, in the form of files or specific content therein, can also be provided by inserting a diskette  
5 containing the information into diskette drive 334 from which client PC 5, under user instruction, will access and read that information from the diskette. Input interfaces 320 contain appropriate circuitry to provide necessary and corresponding electrical connections  
10 required to physically connect and interface each differing dedicated source of input information to client PC 5. Under control of the operating system, application programs 400 exchange commands and data with the external sources, via network connection 9 or path(es) 310, to  
15 transmit and receive information typically requested by a user during program execution.

Input interfaces 320 also electrically connect and interface user input device 395, such as a keyboard  
20 and mouse, to client PC 5. Display 380, such as a conventional color monitor, and printer 385, such as a conventional laser printer, are connected, via leads 363 and 367, respectively, to output interfaces 360. The output interfaces provide requisite circuitry to  
25 electrically connect and interface the display and printer to the computer system.

Furthermore, since the specific hardware components of client PC 5 as well as all aspects of the  
30 software stored within memory 335, apart from the modules that implement the present invention, are conventional

-61-

and well-known, they will not be discussed in any further detail. Generally speaking, agent server 15 and third-party ad server 20 each has an architecture that is quite similar to that of client PC 5.

5

### C. Software

#### 1. Application programs 400

10 FIG. 4 depicts a simplified high-level block diagram of application programs 400 resident within the client PC.

15 As shown, the application programs, to the extent relevant, contain browser 7 and resident JAVA player files 410, i.e., files for JAVA media players that have previously been installed onto the hard disk of the client PC. These players may illustratively include audio, streaming audio, video and multi-media players.

20

Browser 7 contains AdController agent 420, when it has been fully loaded for execution into browser cache, browser disk cache 430 and Java virtual machine 440 (which has been discussed above to the extent relevant). As noted, this agent persists whenever the user causes browser 7 to transition across different web content pages or different web sites, and functions independently and transparently of any such pages and sites. The AdController agent includes applet registry 426 for facilitating inter-applet communication within the agent.

25

30

-62-

The AdController agent contains two applets: Transition Sensor applet 422 and AdController applet 424. As discussed above, the Transition Sensor applet accomplishes three basic functions. First, this applet loads, instantiates and starts the AdController applet. Second, the Transition Sensor applet communicates an Internet address of an advertising server, here server 20, to request an advertisement, specifically an AdDescriptor file therefor, that is to be downloaded and subsequently presented. Lastly, the Transition Sensor applet, through associated click-stream monitoring (performed by a Transition Sensor implemented by this applet), determines when a user situated at client browser 7 undertakes an affirmative action, such as, e.g., causing a mouse click, to request a next successive web page be downloaded and rendered, and so notifies the AdController agent of that event. This event signals a start of an ensuing interstitial interval.

AdController applet 424, which is not embedded in any content page, executes under but is not controlled by browser 7. This applet, also as discussed above, accomplishes several basic functions. First, it creates all other objects that collectively form a run time agent execution module for the agent. As noted above, this includes extending standard Java applet class definitions by over riding standard Java applet init, start, run, stop and destroy life cycle methods. Second, the AdController applet "politely" downloads advertising (including media and, where necessary, player) files, through the client browser executing at a client

-63-

computer, into browser disk cache and in a manner that is transparent to a user situated at the browser. Lastly, the AdController applet interstitially plays advertisements through the client browser in response to the user click-stream associated with normal user navigation across different web pages.

Browser disk cache 430 stores downloaded AdDescriptor files 433 and accompanying and downloaded media and player files 437.

## 2. AdController agent 420

FIG. 5 depicts a high-level block diagram of AdController agent 420.

As shown, the agent specifically contains Transition Sensor applet 422, AdController applet 424 and applet registry 426.

As discussed generally above, the Transition Sensor applet implements, as one of its functions, a transition sensor which detects, through user navigation click-stream monitoring, a user-initiated transition to a new web page, and produces, in response, a corresponding Transition Sensor event. Such a transition occurs in response to an actual user initiated mouse click or key depression to activate a hotlink appearing on a currently displayed content page in order to move to new content page, either on the same site or on another site. Another such transition occurs whenever a stored history

-64-

of web pages just visited by the user changes state. The latter is sensed by a JavaScript function that monitors a history stored in browser disk cache 430 of visited web page URLs and generates an event whenever the history changes state. For ease of reference, we will collectively define the term "click-stream" to encompass any user-initiated transition to a new content page, whether it is a mouse click, key depression or history state change.

10

Transition Sensor events are used to trigger the play of an advertisement only if, by then, all the media and player files for that advertisement have been fully cached into browser disk cache 430. Otherwise, play of that advertisement is deferred until after all those files are cached and the advertisement is ready to be rendered and, importantly, in response to the next user-initiated transition.

15

20

Client browser 7 produces init (initialize) and start and stop Transition Sensor events, as symbolized by line 505 and 510, respectively. The init and start events are produced by the browser to initialize (i.e., load and instantiate) and start the Transition Sensor applet. The stop events are also produced by the browser, though through a Transition Sensor stop method which has been substituted for a standard browser stop method, in response to detection, by the Transition Sensor, of user-initiated page transitions. These events control the state of applet 422. Transition Sensor applet 422 communicates directly with AdController

25

30

-65-

applet 424, as symbolized by line 535 -- such as to pass an Internet address of an advertising server, and indirectly, as symbolized by line 530, through applet registry 426. Registry 426 passes information, as  
5 symbolized by line 540, to AdController applet 424.

As noted above, AdController applet 424 extends standard Java applet class definitions by over riding standard Java applet init, start, run, stop and destroy  
10 life cycle methods. Doing so, particularly in the case of the Stop method (which will be described below in conjunction with FIG. 18), permits the AdController applet to persist in browser disk cache 430 as the user navigates across successive pages and web sites.

15 Advantageously, the AdController applet can readily function in a wide variety of environments, without changes to the coding of the applet itself. This is accomplished through downloading of an external  
20 configuration file (specifically file 620 shown in FIGs. 6A and 6B, which will be discussed below), as part of the applet files, from agent server 15. Suitably changing parameter values in the configuration file permits the behavior of applet 424 to be readily changed  
25 to suit a desired environment without a need to utilize a different version of that applet for each different environment, otherwise requiring different software classes and with attendant modifications and re-compilation.

-66-

Execution of AdController applet 424 begins by Transition Sensor applet 422 calling a standard init Applet method, which downloads the external configuration file, followed by extracting and saving its configuration parameters. These parameters are supplied, as symbolized  
5 by line 515, to the AdController applet, during its execution in order to define its behavior given its current execution environment.

10 As noted above, AdController applet 424 "politely" and transparently downloads advertising (including media and, where necessary, player) files, through browser 7 into browser disk cache 430, for each and every advertisement that is to be subsequently and  
15 interstitially played. A data path through which advertisements are downloaded is shown in FIG. 5 by dot-dashed lines; while that for advertisement play is shown in this figure by dotted lines.

20 Specifically, to download and play advertisements, applet 424 implements Ad Pipeline 545 (which will be discussed in detail below in conjunction with FIG. 14). Pipeline 545 implements various threads (processes) and data structures which collectively load  
25 advertising files into browser disk cache 430 (and, for media files, also into browser RAM cache) and then present fully downloaded advertisements. The pipeline implements Ad Producer, Ad Location and Ad Downloader processes (processes 1500, 1600, 1700 shown in FIGs. 15,  
30 16 and 17, respectively, and discussed in detail below), and download queue 1430 and play queue 1470 (both of

-67-

which are shown in FIG. 14 and discussed in detail below).

5 In essence, once Transition Sensor applet 422, as shown in FIG. 5, supplies AdController applet 424 with a URL of an AdDescriptor file, Ad Pipeline 545 then downloads, as symbolized by dot-dashed line 520, the AdDescriptor file, via agent server 15 (serving as a proxy server), from a remote advertising management  
10 system. As noted above, this file contains a manifest of media and player files necessary to fully play a complete advertisement. Once this AdDescriptor file has been downloaded into Ad Pipeline 545, pipeline 545 then "politely" downloads, as symbolized by line 525, each  
15 file specified in the manifest -- to the extent that file does not already reside on the client hard disk. Pipeline 545 then, once the downloading (to the extent needed) is complete, writes the AdDescriptor file to the play queue and each downloaded file specified therein to  
20 browser disk cache 430; hence forming a queued advertisement for subsequent access.

At the inception of an interstitial interval, signaled by a Transition Sensor stop event, the  
25 AdController applet interstitially plays an advertisement that has then been completely queued -- both in terms of its media and player files. In particular, at the start of that interval, the Ad Pipeline retrieves an AdDescriptor that is then situated at the head of a play  
30 queue. Media players 565 required by that advertisement, as specified in the AdDescriptor file, are started in the

-68-

order specified in that file along with their corresponding media file(s). A resulting processed media stream, produced by the player(s), and as symbolized by line 570, is rendered through browser 7 to the user.

5 Media players 565 may permanently reside, i.e., apart from being downloaded by agent 420, on the client hard disk (thus being implemented by resident player files 410 as shown in FIG. 4) or be downloaded by pipeline 545 into browser disk cache 430 (and also browser RAM cache) for  
10 subsequent access and use (thus stored within files 437 shown in FIG. 4).

Once an advertisement completely plays, AdController applet 424, as shown in FIG. 5, establishes  
15 an appropriate log entry for a "user impression" for that advertisement. Advertisement files are retained in the browser disk cache until that cache completely fills, at which point these files, like any other content files stored in that cache, are deleted by the browser on a  
20 first-in first-out (i.e., age order) basis. Media players 565, browser 7 and browser disk cache 430 are all shown in dashed lines as these components, while being used by the AdController agent, are not viewed as constituting components solely within the agent itself.

25  
FIGs. 6A and 6B collectively depict a high-level flowchart of processing operations 600 performed by AdController agent 420; the correct alignment of the drawing sheets for these figures is  
30 shown in FIG. 6. Though, the operations depicted in this figure -- and also in FIGs. 8, 9A and 9B, 12, and 14-19

-69-

-- occur through a multi-threaded approach to process multiple advertisements on a pipelined basis, to simplify all these figures, the sequential processing flow shown in each of these figures is that which processes a single  
5 common advertisement. Description of threads and classes is provided to the extent needed to provide a sufficient understanding to those skilled in the art as to how these sequential processing flows would preferably be implemented through a multi-threaded Java class  
10 methodology.

Upon entry into process 600 as shown in FIGs. 6A and 6B, which occurs in response to an Transition Sensor init event from browser 7, block 610 is  
15 performed. Through this block, Transition Sensor applet 422 instructs the applet registry to load the AdController applet. Once that occurs, block 615 is performed through which external AdController configuration file 620 is retrieved from agent server 15.  
20 Thereafter, through decision block 630, agent 420 waits, by looping through NO path 631, until browser 7 generates a Transition Sensor start event. When such an event occurs, execution proceeds, via YES path 633 emanating from this decision block, to block 635. Through this  
25 latter block, AdController applet 424 obtains an Internet address of an advertisement management system (e.g., system 25) from which the agent is to retrieve AdDescriptor file 645. Applet 424 then passes this address to Ad Pipeline 545. The Ad Pipeline, as  
30 indicated in block 640, then retrieves AdDescriptor file 645 from this address and particularly through agent

-70-

server 15 serving as a proxy server. Once this file is retrieved, the agent performs block 650 which "politely" downloads all the media and player files 655 (to the extent each file does not already reside on the client hard disk), from advertising management system 25 (residing on advertising server 20), and, through block 660, stores these files into browser disk cache 430 (and, in the case of media files, into browser RAM cache). As noted above, these files are downloaded via agent server 15, which here too serves as a proxy server. This downloading continues until either it finishes or a Transition Sensor stop event generated by the browser arises, whichever occurs first. As to the stop event, decision block 665 tests for its occurrence, with execution looping back, via NO path 666, in the absence of such an event. However, whenever this event occurs, such as (as discussed above) in response to a user-initiated page transition, decision block 665 routes execution, via YES path 668, to block 670. This latter block then, using media players 565, plays an advertisement then fully queued in the play queue on the browser disk cache, i.e., an AdDescriptor file for this ad then resides at a head of the play queue and all associated media and player files for that advertisement, as specified in that AdDescriptor file, then reside on the client hard disk.

-71-

## 3. AdController applet 424

FIG. 7 depicts a high-level block diagram of basic execution threads that implement AdController applet 424.

As shown, in response to a Transition Sensor init event produced by the client browser, one thread executes block 710 to initialize AdController applet 424. This block performs the downloading (to the extent necessary) and instantiation of applet 424. In response to a Transition Sensor start event produced by the client browser, another thread, by executing block 720, starts the AdController applet. Once this applet is started, this applet, in turn and as discussed above, through execution of block 730, enables downloading of advertising (media and player) files to commence. In response to a received Internet address of a remote ad management system (here, e.g., system 25 shown in FIGs. 1B and 1C) supplied by the Transition Sensor applet, a third thread requests, through execution block 740 shown in FIG. 7, an AdDescriptor file from the ad management system situated at this address and then downloads AdDescriptor file 645 received in response. If, by this time, block 730 has enabled advertisement downloading, then advertising files, as specified in AdDescriptor file 645, are "politely" downloaded as required. In response to a Transition Sensor stop event produced by the client browser and which signals an inception of an interstitial interval, another thread, here commencing with execution of block 750, suspends

-72-

downloading of advertisement files in favor of displaying  
a queued advertisement. Once this downloading is  
suspended, this last thread invokes block 760 to commence  
play of an advertisement then situated, in terms of its  
5 AdDescriptor file, at a head of the play queue.

FIG. 8 depicts a high-level flowchart of  
processing operations 800 performed by AdController  
applet 424.

10

Upon entry into operations 800, which occurs in  
response to an init event produced by the Transition  
Sensor applet, block 810 is performed. Through this  
block, the AdController applet is initialized. This  
15 includes downloading files, to the extent needed, for  
this applet from the agent server and then instantiating  
this applet. Once this occurs, block 810 tests for an  
occurrence of AdController start event produced by the  
Transition Sensor applet. Until this event occurs,  
20 execution merely loops back, via NO path 812, to  
block 810. When this event occurs, decision block 810  
routes execution, via YES path 814, to block 815. This  
latter block, retrieves external AdController  
configuration file 620 from the agent server.  
25 Thereafter, block 820 occurs through which the  
AdController applet creates and starts Ad Pipeline 545.  
Once the pipeline is fully started, then, block 825 is  
performed to enable advertisement files to be "politely"  
downloaded into the Ad Pipeline and to thereafter  
30 actually download such files. While advertisement files  
are being downloaded or thereafter, if such downloading

-73-

has completed, decision block 830 tests for an occurrence of a Play Ad event. If no such event occurs, then execution loops back, via NO path 833, to decision block 830 to continue any further downloading. If  
5 however, a Play Ad event occurs, then decision block 830 routes execution, via YES path 837, to block 840. This latter block suspends further downloading of advertisement files into the Ad Pipeline. Once this occurs, then block 845, when performed, issues a request  
10 to the Ad Pipeline to play an advertisement having its AdDescriptor file then located at the head of the play queue. While the advertisement is being played, decision block 850 tests for an occurrence of an shutdown event generated by the browser, such as caused by, e.g., a  
15 user-initiated transition or the user closing an advertisement window or closing the browser itself. If such an event does not occur, decision block 850 routes execution, via NO path 853, back to block 825 to re-enable "polite" download of advertisement files once  
20 again. If such a shutdown event occurs, then processing operations 800 terminate, via YES path 857.

FIGs. 9A and 9B collectively depict a flowchart of processing operations 900 performed by AdController  
25 applet 424 specifically for processing an advertisement; the correct alignment of the drawing sheets for these figures is shown in FIG. 9.

Upon entry into operations 900, block 905 is  
30 performed to receive a request, issued by the Transition Sensor applet, to download a next advertisement,

-74-

specifically a corresponding AdDescriptor file. This request contains an Internet address of a remote ad management system. In response to this request, AdController applet 424 performs block 910 to request Ad Producer process (also being a thread) 1500 to download an ad. The Ad Producer process, as will be discussed below in conjunction with FIG. 15, requests advertisement files, specifically an AdDescriptor file, from an Internet address communicated by the Transition Sensor applet. Thereafter, through block 915, the Ad Producer process blocks (i.e., it actively waits for its input data) until this process receives the Internet address of the remote advertising management system. Thereafter, block 920 executes to cause Ad Location process (also being a thread) 1600 to block until such time as the AdDescriptor file is fully downloaded by Ad Producer process 1500 and is provided to the Ad Location process. Ad Location process 1600, as will be discussed below in conjunction with FIG. 16, performs the following tasks:

(a) on startup of process 1600, this process creates an Ad Producer object; (b) it asks Ad Producer process 1500 for next AdDescriptor file 645; and (c) once process 1600 obtains such AdDescriptor file 645 and if download queue 1430 (see FIG. 14) is not full, it writes that file into this queue. If this queue is then full, process 1600 simply waits until the queue is not full before writing the AdDescriptor file into the queue. Once the AdDescriptor file has been completely downloaded, Ad Location process 1600 inserts, as shown in block 925, this file into download queue 1430.

-75-

Once AdDescriptor file 645 is inserted into the download queue, then Ad Downloader process (also being a thread) 1700 executes. This process, as will be discussed below in conjunction with FIG. 17, performs a single chain of tasks.

First, as shown by block 930, process 1700 blocks until such time as the AdDescriptor file for the advertisement to then be downloaded becomes available in the download queue. During its execution, this process asks download queue 1430 if there is an AdDescriptor file therein, i.e., such a file for which advertising files need to be downloaded. If the download queue is empty, then AdDescriptor process 1700 both waits until that queue is not empty and also retrieves the AdDescriptor file over the network. Once the Ad Downloader process has retrieved the AdDescriptor file, this process downloads, as shown by block 940, all the advertising files specified in the AdDescriptor file, into browser disk cache (and, in the case of media files, into browser RAM cache), by using Browser Cache Proxy 1450 (see FIG. 14). Once all the advertising files have finished downloading, the Ad Downloader process, as shown in block 950, moves the AdDescriptor file to play queue 1470 (see FIG. 14). However, if the play queue is then full, the Ad Downloader process will wait until the play queue is not full before moving the AdDescriptor file into this queue.

The Browser Cache Proxy implements an interface to an abstract cache. The cache implementation could be

-76-

any kind of cache -- the browser disk or RAM cache, a Java virtual memory cache, a local raw disk cache, and so forth. Once passed through this cache proxy, the media files that constitute an advertisement will have been  
5 downloaded into both disk and RAM cache of the browser. Whenever the Ad Downloader process subsequently tries to access any media file having an identical URL to that downloaded, this process will first attempt to load the files from the browser disk cache or browser RAM cache  
10 instead of downloading the file, via the Internet, from its advertising management server; thus leveraging, even across different referring web pages or sites and to the extent possible, a one time download of an advertising file across different advertisements.

15

Next, should a Transition Sensor stop event occur, i.e., indicative of a start of a next interstitial interval, then Transition Sensor stop method 1800 will request that AdController applet 424 then play an  
20 advertisement. In response to this request, an event scheduler thread within the applet will block, as shown in block 955, until such time as applet 424 responds to this request by initiating play of an advertisement. The event scheduler thread controls playing of advertisements  
25 to the user. This process determines when to execute media players specific to the next advertisement in the play queue (i.e., in terms of corresponding AdDescriptor files situated in that queue), as well as provides a callback method which the player executes when that  
30 player has successfully completed presenting an advertisement as specified in its corresponding

-77-

AdDescriptor file. Once the AdController applet has initiated play of an advertisement, then, as shown by block 965, the event scheduler retrieves an advertisement, specifically the corresponding  
5 AdDescriptor file, then situated at the head of the play queue. Thereafter, the event scheduler, as shown in block 970, launches execution of the specific media player(s) 565 (see FIG. 5), as specified in the corresponding AdDescriptor file, to play this particular  
10 advertisement. The browser disk cache provides the associated content files for this advertisement to the media player(s). Once the advertisement has been fully presented, then, as shown in block 975, AdController applet 424 appropriately logs this presentation into a  
15 log file maintained in the browser disk cache for subsequent uploading to the agent server. Execution then exits from operations 900.

A logger process (also implemented as a thread)  
20 keeps track of all log entries that need to be sent back to the agent server. This process simply timestamps entries and adds them to a log buffer. Then, periodically, the logger process will flush the log back to the agent server where those entries can be archived  
25 and analyzed.

For an advertisement, player mechanisms take associated media files specified in the associated AdDescriptor file from the browser cache and actually  
30 display these files to a user via a viewable frame or window. The user will view a pre-cached smoothly playing

-78-

advertisement out of the browser disk cache and, where appropriate for media files, from browser RAM cache, rather than being streamed in over the Internet. Four modes for displaying advertisements are supported; namely, user-event triggered ad play, frame targeted ad play, timer based ad play and PopUp Java frame play. Each of these player mechanisms uses a media player module (contained within media players 565 shown in FIG. 5) and a player thread. The player thread provides an actual presentation of advertising media to the user then operating the client browser. The combination of a player and a player thread provides capabilities of: controlling time-based frequency of advertisement play using an agent configurable timer; displaying advertising media files in a browser window or Java frame; waiting a configurable amount of time (usually the length of the advertisement as specified in its AdDescriptor file); and terminating the advertisement visually upon completion, or at a request of the user if the advertisement, as configured in its AdDescriptor file, permits pre-mature termination.

A frame targeted play renders advertisement media onto a browser window. Such play is interruptible and restartable upon user-demand. Timer based ad play utilizes a separate thread that continuously loops to: obtain an AdDescriptor file from the play queue; display that advertisement using a player and player thread; and sleep for a specified amount of time before repeating this sequence. Timer-based ad play is also interruptible and restartable upon user-demand. The result of this

-79-

type of advertisement play is that the user will periodically view advertisements delivered at regular time intervals rather than by user initiated events. The PopUp Java frame play is a separate thread that also

5 continuously loops to: obtain an AdDescriptor file from the play queue; waits for a signal that a user-initiated transition is occurring; pops up a display window ("pop-up" window) in the browser, for a pre-defined period of time, and presents the advertisement in that

10 window; and removes the pop up window before repeating this sequence. The result of the PopUp Java Player is that the user will view successive advertisements each for pre-defined time interval (which can vary from one advertisement to the next, as specified in the

15 AdDescriptor files for each such advertisement) whenever the user transitions between one web page and the next. Once an advertisement is completely played and in the absence, as discussed above of any instructions in the AdDescriptor file to replay that advertisement, such as

20 through, e.g., timer-based ad play, the associated AdDescriptor file is effectively "pulled off" the play queue.

In particular, downloading of advertisement

25 files occurs, as discussed previously, continuously as effectively a background process, using a separate asynchronous thread. The stop method of the Transition Sensor (specifically Transition Sensor stop method 1800 as will be described below in conjunction with FIG. 18)

30 is responsible for generating a play event to the AdController agent. This event notifies the agent of an

-80-

opportunity to present a downloaded advertisement to the user. This stop method is called automatically by the client browser whenever a user transitions off a web page that contains the embedded advertising tag. In particular, this method invokes a start player method in the AdController agent. The start player method, in turn, invokes a similarly named method, in the event scheduler, which initiates and controls the presentation of advertisements during content page transitions. The event scheduler ensures all media files for an advertisement have been transparently downloaded before their presentation, as well as exercises control over actual execution of the appropriate player classes required to visibly render the advertisement. In that regard, the event scheduler instantiates and invokes a player class appropriate for the current advertisement by calling a start method of that class. This start method creates the player thread that performs visual rendering of the advertisement. Then, this start method calls a run method of the player thread in order to visually present the advertising media from the browser disk and RAM caches. Upon completion, based on the configuration of the advertisement, the run method, by executing its own stop method, terminates the advertisement either upon detecting a close request by the user or completion of ad play timeout. The stop method performs any player software termination and cleanup, finally executing a callback to the scheduler object.

-81-

4. Inter-applet events involving Transition Sensor applet 422

5 FIG. 10 depicts inter-applet events 1000 that occur within AdController agent 420 during execution of Transition Sensor applet 422.

10 As shown and discussed above, whenever a browser interprets and then executes advertising tag 40, specifically tag 42 therein, situated within content page 35, this causes the browser to download script 200 (see FIGs. 2A and 2B) from the agent server. This applet, in turn, dynamically writes Transition Sensor applet 210 into the referring web content page. As  
15 discussed above, once this applet is instantiated executed by the client browser, the applet, in turn, instantiates applet registry 426.

20 Once the applet registry is instantiated, the Transition Sensor queries the registry, this operation being symbolized by line 1015, to determine current status of the AdController applet. If, as symbolized by line 1020, the registry indicates that the AdController applet is not loaded and hence is not executing, then  
25 Transition Sensor applet 422 loads, as symbolized by line 1025, AdController applet 424 from the browser disk cache, and then instantiates and starts this applet. Once the AdController applet is instantiated, the Transition Sensor applet writes, as symbolized by  
30 line 1030, appropriate entries, indicating that both the Transition Sensor applet is loaded and, as symbolized by

-82-

line 1035, that the AdController applet is loaded, into the applet registry. Once this occurs, then the applet registry returns, as symbolized by line 1040, an appropriate handle for the AdController applet to the  
5 Transition Sensor in order to permit the latter to refer to the former. Thereafter, as symbolized by line 1060, the Transition Sensor passes, as discussed above, a request containing an Internet address of an advertisement management system to the AdController  
10 applet to download an AdDescriptor file, for an advertisement, from that address. This address is specified in tag 44 of advertising tag 40 and, as symbolized by dashed line 1050, incorporated into the request. Thereafter, the Transition Sensor, in response  
15 to a user-initiated transition (click-stream) to a next content web page, executes its stop method (method 1800 shown in FIG. 18) to instruct, i.e., issue a request to, as symbolized by line 1065, the AdController applet to play a fully downloaded advertisement having its  
20 corresponding AdDescriptor file then situated at the head of the play queue. Once this occurs, the Transition Sensor applet terminates its execution until the browser next encounters, interprets and executes a content page containing advertising tag 40 at which point the  
25 Transition Sensor applet is re-loaded and re-started; and so forth.

-83-

## 5. Transition Sensor applet 422

FIG. 11 depicts a high-level block diagram of basic processing threads that implement Transition Sensor applet 422.

As shown, in response to a Init (Initialize) Transition Sensor applet event produced by the client browser, a thread commences by executing block 1110 to initialize Transition Sensor applet 422. This thread, in turn, executes block 1120 to load AdController applet 424 from browser disk cache or download it from the agent server, if necessary, and then load it. Thereafter, this thread executes block 1130 to obtain the Internet address of an advertising management system (e.g., system 25 shown in FIGs. 1B and 1C, 2A and 2B, and 10) in tag 44 from advertising tag 40.

As shown in FIG. 11, in response to a Start Transition Sensor applet event generated by the client browser, another thread commences by executing block 1140 to enable Ad Downloader process 1700 (as discussed above, and to be discussed in detail below in conjunction with FIG. 17) to commence "polite" downloading an AdDescriptor file and all required and associated advertisement files (both media and player) into the browser disk cache.

Further, as shown in FIG. 11, in response to a Stop Transition Sensor applet event generated by the client browser, a third thread commences by executing block 1150 to disable Ad Downloader process 1700 and thus

-84-

suspend further downloading of advertisement files. Once this occurs, this thread then executes block 1160 to instruct the AdController applet to play a fully downloaded advertisement having its corresponding AdDescriptor file then situated at the head of the play queue.

FIG. 12 depicts a high-level flowchart of processing operations 1200 performed by Transition Sensor applet 422.

Upon entry in operations 1200, decision block 1210 tests for an occurrence of an init event produced by the client browser. Until such an event occurs, execution loops back, via NO path 1213, to block 1210. When this event occurs, execution proceeds, via YES path 1217 to block 1220 which, when performed, initializes Transition Sensor applet 422. Thereafter, block 1230 is performed through which the Transition Sensor applet 424 instructs, by issuing a request to, the AdController applet to download an advertisement, specifically as discussed above an AdDescriptor file from an ad management server specified in the advertising tag. Once this occurs, decision block 1240 tests for an occurrence of a Transition Sensor start event generated by the client browser. Until such an event occurs, execution loops back, via NO path 1243, to block 1240. When this particular event occurs, execution proceeds, via YES path 1247 to block 1250 which, when performed, enables Ad Pipeline 545 to download the AdDescriptor file and associated advertising files.

-85-

Next, decision block 1260 tests for an occurrence of a Transition Sensor stop event generated by the client browser. Until such an event occurs, execution loops back, via NO path 1263, to block 1260.

5 When a Transition Sensor stop event occurs, execution then proceeds, via YES path 1267 to block 1270 which, when performed, requests that AdController applet 424, specifically via Ad Pipeline 545, then play an advertisement.

10

6. Ad Loader process 1300

FIG. 13 depicts a high-level block diagram of Ad Loader process 1300 which forms a portion of  
15 AdController applet 424. Process 1300 provides an advertiser (specifically an advertising programmer) with control over various functions, for advertisement play and logging, implemented by the AdController applet, specifically how and where this applet retrieves  
20 advertisements across a networked connection and how those advertisements are played. Through use of the Ad Loader, the AdController applet can be controlled, to an extent desired, by external programmatic calls.

25

As shown, this process includes Ad Loader API (application programming interface) 1310 which interfaces to Ad Pipeline 545 and through this pipeline controls how advertisements are presented, as symbolized by  
block 1370, by the player mechanisms. In particular, the  
30 Ad Loader API provides information regarding and, through setting various program variables, permits programmer

-86-

control over advertisement display and downloading operations. In that regard, these variables provide a callback to the AdController applet indicating when a content page to which the user has just transitioned has completed its downloading; and can be used to: instruct the AdController applet when to download a next advertisement, when to play a next advertisement fully queued in the Ad Pipeline, start and stop a play timer (for use with, e.g., timer based ad play, as discussed above), log a message, set a mode so as to specify a desired location to display advertisements, suspend and resume download of advertisement files into the Ad Pipeline, suspend a current download for a given period of time, and suspend and resume advertisement play by the player mechanisms.

In that regard, the Ad Loader API configures Ad Pipeline 545 such that AdDescriptor file 645 is downloaded, as symbolized by block 1320, from a remote ad management system into the Ad Pipeline in response to receipt of an Internet address of an ad management system and, for targeted advertisements, a URL of a referring web page address. As symbolized by block 1330, the API configures the Ad Pipeline such that advertisement downloading is enabled only when AdController applet 424 is not playing an advertisement. Furthermore, as symbolized by block 1340, the API configures the Ad Pipeline such that advertisement downloading is disabled whenever the AdController applet is playing an advertisement. Furthermore, as symbolized by block 1350, the API configures the Ad Pipeline such that

-87-

advertisement play is to commence in response to a request to play a next advertisement, i.e., one that is fully cached in the browser disk cache and having its AdDescriptor file then situated at the head of the play queue.

#### 7. Ad Pipeline 545

FIG. 14 depicts a high-level block diagram of Ad Pipeline 545. As discussed above, the Ad Pipeline implements various threads and data structures which collectively load advertising files (needed media and player files) into the browser disk cache and, for media files, also into browser RAM cache, and then present fully downloaded advertisements. As noted, the Ad Pipeline employs Ad Producer process 1500, Ad Location process 1600 and Ad Downloader process 1700 (all of these processes, as noted above, are also threads).

In response to an incoming request to download an advertisement, Ad Pipeline 545 is invoked. Specifically, within this pipeline, first block 1410 executes to invoke Ad Producer process 1500 in response to an incoming request to download an advertisement. As discussed above, this request, issued by the Transition Sensor applet, includes an Internet address of a remote ad management system (e.g., system 25 shown in FIGs. 1B and 1C) on which an advertisement resides and is to be downloaded (through agent server 15 as a proxy server). Ad Producer process 1500, as will be discussed below in conjunction with FIG. 15, requests advertisement files,

-88-

specifically an AdDescriptor file (e.g., file 645), from an Internet address specified in the request. During its execution, the Ad Producer process waits until it receives the Internet address of the remote advertising management system, whereupon this process then downloads AdDescriptor file 645 from the specified ad management system. Once this file has been downloaded, block 1420, shown in FIG. 14, executes to invoke Ad Location process 1600 (which will be discussed in detail below in conjunction with FIG. 16). During its execution, Ad Location process 1600 blocks until such time as AdDescriptor file 645 is fully downloaded by Ad Producer process 1500 and is provided to the Ad Location process, whereupon the Ad Location process writes this AdDescriptor file into download queue 1430.

After AdDescriptor file 645 has been written into the download queue, Ad Location process 1600, as will be discussed below in conjunction with FIG. 16, performs the following tasks: (a) on startup of process 1600, this process creates an Ad Producer object; (b) this process asks Ad Producer process 1500 for next AdDescriptor file 645; and (c) once process 1600 obtains AdDescriptor file 645 and, if download queue 1430 is not full, process 1600 writes that file into this queue. If this queue is then full, process 1600 simply waits until the queue is not full before writing the AdDescriptor file into the queue. Once the AdDescriptor file has been completely downloaded, Ad Location process 1600 inserts, as shown in block 925, this file into download queue 1430.

-89-

Once AdDescriptor file 645 is inserted into the download queue, then block 1440 executes to invoke Ad Downloader process 1700. Process 1700, which will be discussed below in conjunction with FIG. 17, performs a single chain of tasks. First, process 1700 blocks until such time as the downloaded AdDescriptor file has become available in the download queue. During its execution, this process asks download queue 1430 if it contains an AdDescriptor file, e.g., file 645. If so, then advertising files need to be downloaded for that particular AdDescriptor file. If the download queue is empty, then process 1700 both waits until that queue is not empty and also retrieves the AdDescriptor file over the network. Once Ad Downloader process 1700 has obtained this AdDescriptor file, process 1700 then downloads, all the media and required player files specified in the AdDescriptor file by using Browser Cache Proxy 1450, into browser disk (and RAM) cache 1460. Once all the advertising files have finished downloading, process 1700 moves the AdDescriptor file to play queue 1470. However, if the play queue is then full, the Ad Downloader process waits until play queue 1470 is not full before moving the AdDescriptor file into this queue for subsequent ad play. As discussed above, AdDescriptor file 645 for a fully queued ad (i.e., with its all the associated media and player residing on the client hard disk) is subsequently retrieved from play queue 1470 in response a request to play an advertisement, this request being issued in response to a Transition Sensor stop event.

-90-

## 8. Ad Producer process 1500

FIG. 15 depicts a high-level block diagram of Ad Producer process 1500. As noted above, this process requests an AdDescriptor file from an Internet address communicated by the Transition Sensor applet and subsequently downloads that file in the browser disk cache.

As shown, upon entry into process 1500, execution first proceeds to decision block 1510. This block determines whether a URL has been received, from the Transition Sensor, from which to fetch an AdDescriptor file. If such a URL has not yet been received, then execution loops back, via NO path 1517, to this decision block. Alternatively, if such a URL has been received, then execution proceeds, via YES path 1513, to block 1520 which, in turn, stores this URL, as Ad URL 1530, for use during a next successive advertisement download opportunity.

Once this URL has been so stored, execution proceeds to decision block 1540. This block tests for an occurrence of a user-initiated event (click-stream) signifying that advertisement downloading can now occur, such as, e.g., when the user has just closed an existing advertisement frame and a next successive content page to which the user has transitioned is being rendered by the client browser. If such an event has not yet occurred, e.g., the next successive content web page is downloading, then execution merely loops back, via NO

-91-

path 1543, back to decision block 1540. However, if such an event occurs, then this decision block routes execution, via YES path 1547, to block 1550. This latter block, when executed, downloads AdDescriptor file 645 using the URL communicated by the Transition Sensor. Once this file is completely downloaded, then block 1560 executes to transfer this file to Ad Location process 1600. Thereafter, execution loops back, via path 1565, to decision block 1510, and so forth.

9. Ad Location process 1600

FIG. 16 depicts a high-level block diagram of Ad Location process 1600. This process, as discussed above, accomplishes the following tasks: (a) on startup of this process, process 1600 creates an Ad Producer object; (b) process 1600 asks Ad Producer process 1500 for next AdDescriptor file 645; and (c) once process 1600 obtains AdDescriptor file 645 and, if download queue 1430 (see FIG. 14) is not full, process 1600 then writes that file into this queue. If this queue is then full, process 1600 simply waits until the queue is not full before writing the AdDescriptor file into the queue.

Upon entry into process 1600 and with respect to advertisement downloading itself, execution proceeds to decision block 1610. This decision block, when executed, determines whether an Internet address (URL) of an ad management system has been received from the Transition Sensor applet for a next successive advertisement download. If that address has not yet been

-92-

received, then execution merely loops back, via NO path 1613, to decision block 1610. Alternatively, if such an address has been received but not yet processed, then decision block 1610 routes execution, via YES path 1617, to block 1620. This latter block requests Ad Producer process 1500 to download an AdDescriptor file, e.g., file 645, from this URL. Once this request occurs, execution proceeds to decision block 1630 to determine whether this AdDescriptor file has been completely downloaded. If this file download is still occurring, then execution merely loops back, via NO path 1633, to block 1630 to await completion of the download. Once this download completes, decision block 1630 routes execution, via YES path 1637, to block 1640. This latter block writes the downloaded AdDescriptor file into download queue 1430 (providing this queue is not full). Once this occurs, execution is directed, via path 1645, back to decision block 1610, and so forth.

#### 10. Ad Downloader process 1700

FIG. 17 depicts a high-level block diagram of Ad Downloader process 1700. Essentially, as discussed above, process 1700 determines, from the download queue, if that queue contains an AdDescriptor file, e.g., file 645. If it does contain such an AdDescriptor file, then advertising files need to be downloaded for that file. Consequently, process 1700 then downloads required advertising files specified in that AdDescriptor file. Once this fully occurs, process 1700 moves the AdDescriptor file to the play queue.

-93-

In particular upon entry into process 1700, execution proceeds to decision block 1710. This decision block determines whether the download queue then contains an AdDescriptor file, e.g., file 645. If the queue is empty, then execution merely loops back, via NO path 1717, to this decision block to await such an AdDescriptor file. However, if download queue 1430 then contains such a file, process 1720 obtains the AdDescriptor file then situated at the head of this queue. Thereafter, block 1730 executes. This block downloads all the required advertising files, not then resident on the client hard disk, into browser proxy cache 1450. This block also transfers all the associated media files in the browser proxy cache to the browser RAM cache. Execution then proceeds to decision block 1740 which determines whether all required advertising files have then been downloaded. If any such file remains to be downloaded, then decision block 1740 routes execution, via NO path 1747, back to block 1730 to download that file. Alternatively, if all the required advertising files have been downloaded, then execution proceeds, via YES path 1743, to block 1750. This latter block moves the AdDescriptor file from download queue 1430 to an end of play queue 1470. Once the AdDescriptor file is written into the play queue, the corresponding advertisement is then ready to be presented to the user, in order relative to other AdDescriptor files then queued in the play queue, during an ensuing interstitial interval.

-94-

## 11. Transition Sensor stop method 1800

FIG. 18 depicts a flowchart of stop method 1800 invoked by Transition Sensor applet 422. This method, in response to a stop event generated by the browser, suspends downloading of advertisement files and initiates interstitial ad play.

In particular, upon entry into method 1800, decision block 1810 executes to determine if a stop event has been received from browser 7. If such a stop event has yet not occurred, then execution loops back, via NO path 1813, back to block 1810 to await occurrence of this event. When this event occurs, decision block 1810 directs execution, via YES path 1817, to decision block 1820. This latter decision block determines if AdController applet 424 is then loaded and executing. If this applet is not then executing, decision block 1820 routes execution, via NO path 1827, to block 1830. This latter block inhibits any request from being made to the AdController applet to play any advertisement until that applet is executing and, once that occurs, a next user-initiated (click-stream) event occurs. Thereafter, execution of method 1800 terminates. Alternatively, if the AdController applet is loaded and executing, then decision block 1820 routes execution, via YES path 1823, to block 1840. This latter block requests the AdController applet to play a next advertisement. Once this request is issued, then execution proceeds to block 1850. This block, in turn, requests the AdController applet to suspend "polite" background

-95-

downloading of advertisement files while a next successive web content page, as requested by the user, is being downloaded by the browser. Once block 1850 executes, execution of method 1800 terminates.

5

## 12. Transition Sensor start method 1900

FIG. 19 depicts a flowchart of start method 1900 invoked by Transition Sensor applet 422.

10 This method, in response to a start event generated by the browser, resumes background downloading of advertisement files.

Specifically, upon entry into method 1900, execution proceeds to decision block 1910 which, when executed, determines if a start event has been received from browser 7. If such a start event has not yet occurred, then execution loops back, via NO path 1913, back to block 1910 to await occurrence of this event. When this event occurs, decision block 1910 directs execution, via YES path 1917, to decision block 1920. This latter decision block determines if AdController applet 424 is then loaded and executing. If this applet is not then executing, decision block 1920 routes execution, via NO path 1927, to block 1930. Block 1930 inhibits any request from being made to the AdController applet to download any advertisement until that applet is executing and, once that occurs, a next user-initiated (click-stream) event occurs. Once the AdController applet begins executing and thereafter a next user-initiated (click-stream) event occurs, execution

15  
20  
25  
30

-96-

proceeds to block 1940. This latter block requests the AdController applet to resume background downloading of advertisement files. Once this downloading is resumed, method 1900, through execution of block 1960, waits for  
5 browser 7 to call Transition Sensor stop method 1800 whenever the user next unloads a web page currently rendered by the browser, i.e., causes a user initiated-event to transition to a next successive web page. Alternatively, if the AdController applet is  
10 loaded and executing, then decision block 1920 routes execution, via YES path 1923, to block 1950. Since at this point the next successive content web page has been fully executed by the browser and is, e.g., rendered to the user, block 1950 issues a request, through the applet  
15 registry, to the AdController applet to enable it to resume background downloading of advertisement files. Once this occurs, block 1940 is executed to issue a request to the AdController applet to resume the background downloading. Execution then proceeds to  
20 block 1960 to wait for browser 7 to call Transition Sensor stop method 1800 whenever the user next unloads a web page currently rendered by the browser, i.e., causes a user initiated-event to transition to a next successive web page. Whenever the browser generates a next  
25 Transition Sensor stop event, process 1900 terminates.

Although a single embodiment which incorporates the teachings of our present invention has been shown and described in considerable detail herein, those skilled in  
30 the art can readily devise many other embodiments and


-97-


applications of the present invention that still utilize these teachings.

-98-

We claim:

- 1     1.   A computer readable medium storing a web page  
2     wherein the web page comprises a plurality of computer  
3     readable instructions, the instructions representing page  
4     content and an embedded advertising tag, wherein the  
5     advertising tag when executed by a web browser, causes  
6     the browser to:  
7         download from a server, at least one media file  
8     forming a predefined advertisement, while the browser is  
9     displaying a content web page to a user; and  
10        during an interstitial interval occurring in  
11    response to a user-initiated event for transitioning  
12    between successive web pages, suspending the download and  
13    displaying said one media file so as to render the  
14    advertisement through the browser to the user.










FIG. 1F

FIG. 1D

FIG. 1E
FIG. 1F

FIG. 2A




FIG. 2

FIG. 2A	FIG. 2B
---------	---------




FIG. 2B




FIG. 3




FIG. 4





FIG. 5

FIG. 6A  
AdController  
AGENT  
Processing






FIG. 6A

FIG. 6B

FIG. 6

FIG. 7






FIG. 8  
AdController  
APPLET  
Processing








FIG. 9

FIG. 9A

FIG. 9B

FIG. 10






FIG. 11









FIG. 13







FIG. 15 - Ad Producer Process

FIG. 16 - Ad Location Process






FIG. 17 - Ad Downloader Process




FIG. 18 - Transition Sensor Stop Method




FIG. 19 - Transition Sensor Start Method

**# Section 1 - Applet Player Java Class Configuration**

playerName=AppletViewerPopup

playerClass=com.unicast.adcontroller.players.AppletViewerPopup

**# Section 2 - Ad Java Classes Configuration**

AppletViewerPopup.adAppletName=ANM\_AnimationLoaderApplet

AppletViewerPopup.adAppletClass=

com.pointcast.applets.AnimationApplet.ANM\_AnimationLoaderApplet

**# Section 3 - Player Execution Configuration**

AppletViewerPopup.windowTitle=AdController PointCast Ad

AppletViewerPopup.playerRefreshRate=1000

AppletViewerPopup.allowExit=true

AppletViewerPopup.xPosition=50

AppletViewerPopup.yPosition=50

AppletViewerPopup.windowWidth=280

AppletViewerPopup.windowHeight=355

AppletViewerPopup.isResizable=false

AppletViewerPopup.secondsWindowsOpen=180

AppletViewerPopup.secondsToOverlay=1

AppletViewerPopup.closeButtonLabel=Close

AppletViewerPopup.openButtonLabel=More Info

AppletViewerPopup.saveButtonLabel=Save

AppletViewerPopup.openURL=http://www.pointcast.com/

**# Section 4 - Ad Applet Configuration****# A. Ad Applet DocumentBase**

AppletViewerPopup.ANM\_AnimationLoaderApplet.documentBase=

http://www2.unicast.com/~rlandsma/AdController/MacromediaApplet/

**# B. Ad Applet Parameters**

AppletViewerPopup.ANM\_AnimationLoaderApplet.AdToPlay=deepsea.anm

AppletViewerPopup.ANM\_AnimationLoaderApplet.AltImage=test.gif

AppletViewerPopup.ANM\_AnimationLoaderApplet.MaxCycles=5

AppletViewerPopup.ANM\_AnimationLoaderApplet.TargetURL=http://www.pointcast.com/

AppletViewerPopup.ANM\_AnimationLoaderApplet.TargetFrame=\_top

AppletViewerPopup.ANM\_AnimationLoaderApplet.BorderWidth=2

AppletViewerPopup.ANM\_AnimationLoaderApplet.BorderType=Standard

**# C. Ad Applet MediaList**

AppletViewerPopup.ANM\_AnimationLoaderApplet.mediaURLList=new

AppletViewerPopup.ANM\_AnimationLoaderApplet.mediaURLList.size=2

AppletViewerPopup.ANM\_AnimationLoaderApplet.mediaURLList.element0=deepsea.anm

AppletViewerPopup.ANM\_AnimationLoaderApplet.mediaURLList.element1=animApplet.jar

2000

**FIG. 20 - ILLUSTRATIVE AD DESCRIPTOR  
FILE CONTENTS FOR A POINTCAST  
JAVA AD**

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/10707

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G06F17/60

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 818 742 A (IBM) 14 January 1998 (1998-01-14) column 2, line 15 -column 3, line 32 column 4, line 45 -column 7, line 2 ---	1
X	KOHDA Y ET AL: "UBIQUITOUS ADVERTISING ON THE WWW: MERGING ADVERTISEMENT ON THE BROWSER" COMPUTER NETWORKS AND ISDN SYSTEMS, vol. 28, 1 May 1996 (1996-05-01), pages 1493-1499, XP002037594 ISSN: 0169-7552 the whole document ---	1
A	WO 97 21183 A (BELL COMMUNICATIONS RES) 12 June 1997 (1997-06-12) abstract page 3, line 8 -page 10, line 25 -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

16 September 1999

Date of mailing of the international search report

23/09/1999

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Abbing, R

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/10707

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0818742 A	14-01-1998	GB 2315140 A JP 10133838 A	21-01-1998 22-05-1998
WO 9721183 A	12-06-1997	CA 2240009 A	12-06-1997